




R410A All DC Inverter VRF V5 P Series 50/60Hz

COMMERCIAL AIRCONDITIONERS



***DC Inverter
VRF V5 P Series
50/60Hz***

Contents

- ▶ 05 **Features**
- ▶ 14 **Specifications**
- ▶ 19 **Indoor units lineup**
- ▶ 53 **Control systems**
- ▶ 80 **HRV**
- ▶ 83 **Branch pipes**

Features

Specifications

Indoor units lineup

Control system

HRV

Branch pipes

Features

Wide Application Range

Large capacity for big sized building

The outdoor units' capacity range from 8HP up to 88HP in 2HP increment, max. combination of 4 basic models.

8,10,12HP



14,16,18,20,22HP



24~44HP



46~66HP



68~88HP




Wide choices of locations

Maximum 64 indoor units with capacity up to 130% of total outdoor units' can be connected in one refrigeration system. It is especially suitable for office buildings, hotels, apartments, waiting rooms, hospitals, and so on.



Long piping length



The solution supports an incredible piping length of 1,000m(3280ft.) and level difference of 110m(360.8ft.), making it perfect for large projects.

		Permitted value	
		m	ft.
Piping length	Total pipe length*(Actual)	1000	3280
	Maximum piping(L)	Actual length	175
		Equivalent length	200
	Piping (From the first IDU branch to the farthest IDU) equivalent length	40/90*	131.2/295.2*
Level difference	Level difference between IDU-ODU	Outdoor unit up	90
		Outdoor unit down	110
	Level difference between IDU-IDU	30	98.4

*Total pipe length is equal to two times orange pipe length plus blue pipe length.

*When the fastest pipe length is more than 40m(131.2ft.). It needs to meet the specific condition according to the installation part of the technical service manual.

High external static pressure


The high-static pressure propeller and optimized fan guard can adapt to various installation environments.

Koolman now offers up to 60Pa(0.24"W.G.)* external static pressure units for customized applications. A standard 0-20Pa(0-0.08"W.G.) function is equipped by default.

*You need to consult Koolman if you require over 60Pa(0.24"W.G.).



Wide operation range




The V5 P series system operates stably at extreme temperatures ranging from -20°C(-4°F) to 48°C(118.4°F).

Higher Reliability

Duty cycling

In one combination, any outdoor unit can run as the master outdoor unit to equalize the service life of all units.



Back-up function


In a multiple system, when the master unit failed, any single unit can be set as the master unit, then the remaining units can keep on working. This can be set on PCB by DIP switches at site.



High efficiency oil balance and oil return technology


5 stages oil control technology ensures every outdoor unit & compressor's oil always keep in the safe level, completely solve the compressor oil shortage problem.

- **1st stage:** compressor internal oil separate.
- **2nd stage:** high efficiency centrifugal oil separator (separation efficiency up to 99%) makes oil separate from discharge gas and go back to compressors.
- **3rd stage:** oil balance pipes between compressors ensure even oil distribution to keep compressors running normally.
- **4th stage:** oil balance pipes among modules ensure even oil distribution among modules.
- **5th stage:** Auto oil return program by monitoring the running time and state of system ensures reliable oil return.



Accurate control technology

- Double EXV and liquid side by pass solenoid valve in one system, each EXV part achieves 480 pulse to adjust flow precisely, total 960 pulse. All the solenoid valves equipped in the unit ensure temperature-control precisely, system running steadily and economically.
- 2000 pulses EXV is used in some indoor units to ensure precise refrigerant control and less temperature fluctuation for comfortable room environment.



Real-time pressure control technology

- The pressure sensor can monitor the high pressure of the system and send it to the mainboard all the time.
- The system controls the speed of DC fan motor according to the load and the high pressure, so that the pressure can be regulated precisely.
- The system can operate in the best pressure status under different working environment, the reliability will be higher and the lifespan of the system will be longer.



Temperature protection for electricity device



- Professional air outlet grille design, cool down control box temperature around 8°C(14.4°F).
- High temperature protection for PCB box, auto recover when temperature back to normal.

Various kinds of protect function



Ground protection



Phase sequence protection




Default phase protection



High-voltage protection



Low-voltage protection



Current protection



Fan motor Temp. protection



Compressor overload protection



Compressor Temp. protection




Pressure protection

Enhanced Comfort

Intelligent soft start technology

All DC inverter compressor and soft start function reduce strike to the electric network. This high-performance and low noise DC inveter compressor operates at a faster rate when starting, reducing start-up time. It also helps the unit to quickly adjust the room temperature to the set level.


Comparison of start by inverter and by traditional methods



Quick warm-up and cool-down design


By utilizing the benefits of all DC inverter compressors, the system can reach full load quickly and shorten the warm-up and cool-down times to provide an immediate and comfortable air solution. Less temperature fluctuation will create a better living environment.

Fluctuation of room temperature



Intelligent defrosting technology

Intelligent defrosting program will judge the defrosting time according to the system real requirement, reduce the heating loss by unnecessary defrosting and make the indoor side more comfortable.



Optional operation mode

5 operation modes to be chosen:

- Heating priority mode (default)
- Cooling priority mode
- Heating only mode
- Cooling only mode
- VIP or Voting priority mode (No. 63 IDU or majority requirement priority)



Heating priority (default)



Cooling only



Vote priority



Cooling priority



Heating only



VIP priority

Advanced silence technology

- Improved air outlet grille
- Anti vibration motor mounting frame


- CFD designed new shape fan blade
- 3+4 fan blade design

- All DC inverter compressors
- Compressor noise enclosure

- All DC inverter fan motors
- Night silent mode




3+4 fan blade, patent design



Outdoor unit night silent mode

- Koolman's Night Silent Mode feature which is easily set on the PCB board allows the unit to be set to varies time options during Non-peak and Peak operation time optimizing the units noise output. Extra silent operation mode can reduce sound level further, minimum 43dB (A).
- Night silent operation will be activated X hours after the peak temperature during daytime, and it will go back to normal operation after Y hours.





Indoor unit silent mode





According to users' needs real time or the room temperature, users can set the SILENT MODE through the indoor wired controller KJR-29B (optional). The minimum noise degree is 22.5dB(A) (for the 1.5kW compact four-way cassette).

High Efficiency

V5 P Series achieves the industry's top class energy efficiency of cooling and heating by utilizing DC compressor control, DC Fan motor, and improved performance heat exchanger.





High efficiency DC inverter compressor




Smooth 180°sine wave DC inverter

Smooth the rotation of the compressor motor, improve the compressor operation efficiency sharply. Effectively control the harmonic current and electromagnetic noise, and fully pass the international EMC test.




All DC inverter compressor, auto energy allocation

Thanks to the all DC inverter compressors technology, the running unit's output will automatically adjust according to the real time load demands. Units are always running at 40-70Hz which is the most efficient range. It makes units cost less energy and keep in good condition.



New profile fan blade



- A new CFD designed blade with concave suction surface changes the distribution of surface pressure.
- Through restraining the development of secondary currents, decreases the drop loss of wall air current.
- A new blade with sharp edges and a slight curve increases the airflow rate and lowers vibration and airflow resistance.




DC fan motor

According to the running load and pressure, it controls the speed of DC fan to achieve the minimum power consumption.

- Used across entire range of models (from 8 to 88 HP).
- Efficiency improvement up to 45% especially at low speed.
- Wide speed adjustment with 18 steps vector control.



High performance heat exchanger




- The new designed window fins enlarge the heat-exchanging area, decrease the air resistance, save more power and enhance heat exchange performance.
- Hydrophilic film fins and inner-threaded copper pipes optimize heat exchange efficiency.
- When the outdoor temperature is 35°C(95°F), the refrigerant can be cooled down to 37.1°C(98.8°F), thus achieving high heat-exchanging efficiency with only 2.1°C(3.8°F) temperature difference.

Easier Installation and Service

Simple communication wiring

Centralized controller (CCM30) can connect from indoor side or outdoor side (XYE terminals) at will. With one group of wires, we can realize the network communication and system communication. Such simple wiring is more convenient for installation work at site.




Auto-test operation and auto-addressing function

- Just simply press the test operation button, the unit will perform an automatic system check, including wiring, shutoff valves, and sensors. The results are returned automatically after the check is finished.
- Outdoor unit can distribute addresses for indoor unit automatically. Wireless and wired controllers can query and modify each indoor unit's address.



Rotatable electric control box

- The newly designed rotating control box is so excellent that it can rotate in maximum 150 degree. It is convenient for the inspection and maintenance of the pipeline system and greatly reduced the time of dismount the electric control box.
- Checking window for quick inspection of system status.




360° pipe connection

Pipes can be connected in multi directions: front, left, right and rear.



Compact size for saving space

Compact size design minimizes the installation footprint, and is easier for transportation. The units can even be transported through elevator or forklift at the jobsite.



Specifications

Recommended combination table

Model	N° of Outdoor Units	N° of Compressors	Outdoor Unit Combination								Maximum N° of Connectable Indoor Units	Capacity	
			8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP		Cooling (kW)	Heating (kW)
8HP	1	1	1								13	25.2	27.0
10HP	1	1		1							16	28.0	31.5
12HP	1	1			1						20	33.5	37.5
14HP	1	2				1					23	40.0	45.0
16HP	1	2					1				26	45.0	50.0
18HP	1	2						1			29	50.0	56.0
20HP	1	2							1		33	56.0	63.0
22HP	1	2								1	36	61.5	69.0
24HP	2	2			2						39	67.0	75.0
26HP	2	3		1			1				43	73.0	81.5
28HP	2	3		1				1			46	78.0	87.5
30HP	2	3		1					1		50	84.0	94.5
32HP	2	3		1						1	53	89.5	100.5
34HP	2	3			1					1	56	95.0	106.5
36HP	2	4						2			59	100.0	112.0
38HP	2	4					1			1	63	106.5	119.0
40HP	2	4						1		1	64	111.5	125.0
42HP	2	4							1	1	64	117.5	132.0
44HP	2	4								2	64	123.0	138.0
46HP	3	4			2					1	64	128.5	144.0
48HP	3	5		1			1			1	64	134.5	150.5
50HP	3	5		1				1		1	64	139.5	156.5
52HP	3	5		1					1	1	64	145.5	163.5
54HP	3	5		1						2	64	151.0	169.5
56HP	3	5			1					2	64	156.5	175.5
58HP	3	6						2		1	64	161.5	181.0
60HP	3	6					1			2	64	168.0	188.0
62HP	3	6						1		2	64	173.0	194.0
64HP	3	6							1	2	64	179.0	201.0
66HP	3	6								3	64	184.5	207.0
68HP	4	6			2					2	64	190.0	213.0
70HP	4	7		1			1			2	64	196.0	219.5
72HP	4	7		1				1		2	64	201.0	225.5
74HP	4	7		1					1	2	64	207.0	232.5
76HP	4	7		1						3	64	212.5	238.5
78HP	4	7			1					3	64	218.0	244.5
80HP	4	8						2		2	64	223.0	250.0
82HP	4	8					1			3	64	229.5	257.0
84HP	4	8						1		3	64	234.5	263.0
86HP	4	8							1	3	64	240.5	270.0
88HP	4	8								4	64	246.0	276.0

Notes:
 Capacities are based on the following conditions:
 Cooling: Indoor temperature 80.6°F(27°C) DB/66.2°F(19°C) WB; Outdoor temperature 95°F(35°C) DB/75.2°F(24°C) WB.
 Heating: Indoor temperature 68°F(20°C) DB/59°F(15°C) WB; Outdoor temperature 44.6°F(7°C) DB/42.8°F(6°C) WB.
 Piping length: Interconnecting piping length is 24.6ft.(7.5m), level difference is zero.
 The above combination models are factory-recommended models.

Outdoor specifications (380~415V-3Ph-50/60Hz)

Model			KVF-H2523EQD	KVF-H2803EQD	KVF-H3353EQD	KVF-H4003EQD
Power supply			V/Ph/Hz	380~415/3/50(60)		
Cooling	Capacity	kW	25.2	28.0	33.5	40.0
		RT	7.2	8.0	9.5	11.4
		kBtu/h	86.0	95.5	114.3	136.5
		kcal/h	21,672	24,080	28,810	34,400
	Power input	kW	5.79	7.02	8.71	10.81
	EER	kW/kW	4.35	3.99	3.85	3.7
Heating	Capacity	kW	27.0	31.5	37.5	45.0
		RT	7.7	9.0	10.7	12.8
		kBtu/h	92.1	107.5	128.0	153.5
		kcal/h	23,220	27,090	32,250	38,700
	Power input	kW	5.79	7.19	8.82	10.98
	COP	kW/kW	4.66	4.38	4.25	4.10
Connectable indoor unit	Total capacity	%	50-130			
	Max. quantity		13	16	20	23
Sound pressure level		dB(A)	57	57	58	60
Pipe connections	Liquid pipe	in.(mm)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)
	Gas pipe	in.(mm)	Φ7/8(Φ22.2)	Φ7/8(Φ22.2)	Φ1(Φ25.4)	Φ1(Φ25.4)
	Oil balance pipe	in.(mm)	Φ5/16(Φ8)			
Fan motor	Type		Axial propeller			
	Quantity		1	1	1	2
	Air flow rate	m³/h	12,000	12,000	12,000	14,000
		CFM	7,060	7,060	7,060	8,240
	Motor output	W	465	465	465	290+230
	ESP	in.WG(Pa)	0-0.08(0-20)(default)			
in.WG(Pa)		0.08-0.24(20-60)(customized)				
DC inverter compressor	Quantity		1	1	1	2
	Capacity	kW	31.59	31.59	23.25	13.8×2
		kBtu/h	107.8	107.8	79.3	47.1×2
	Crankcase heater	W	27.6×2	27.6×2	27.6×2	27.6×4
	Oil type		FVC68D			
Oil charge		gal.(ml)	0.132(500)	0.132(500)	0.132(500)	0.132(500)×2
Refrigerant	Type		R410A			
	Factory charging	lbs.(kg)	20(9)	20(9)	24(11)	29(13)
Design pressure (High/Low)		MPa	4.4/2.6			
		PSI	640/380			
Net dimension (W×H×D)		inch	39×64-3/8×31-1/8			52-3/4×64-3/8×31-1/8
		mm	990×1635×790			1340×1635×790
Packing size (W×H×D)		inch	41-1/2×71-1/16×33-5/8			55-3/8×71-1/16×33-5/8
		mm	1055×1805×855			1405×1805×855
Net weight		lbs.(kg)	483(219)	483(219)	523(237)	655(297)
Gross weight		lbs.(kg)	516(234)	516(234)	556(252)	695(315)
Operating temperature range	Cooling	°F(°C)	23~118.4(-5~48)			
	Heating	°F(°C)	-4~75.2(-20~24)			

Notes:

Capacities are based on the following conditions:

Cooling: Indoor temperature 80.6°F(27°C) DB/66.2°F(19°C) WB; Outdoor temperature 95°F(35°C) DB/75.2°F(24°C) WB.

Heating: Indoor temperature 68°F(20°C) DB/59°F(15°C) WB; Outdoor temperature 44.6°F(7°C) DB/42.8°F(6°C) WB.

Piping length: Interconnecting piping length is 24.6ft.(7.5m), level difference is zero.

Connection piping diameter is based on the condition that the total equivalent liquid length is less than 295.2ft.(90m). When the total equivalent liquid length is more than 295.2ft.(90m), please refer to technical manual to choose the connection piping diameter.

Sound values are measured in a semi-anechoic room, at a position 3.28ft.(1m) in front of the unit and 4.26ft.(1.3m) above the floor.

Outdoor specifications (380~415V-3Ph-50/60Hz)

Model			KVF-H4503EQD	KVF-H5003EQD	KVF-H5603EQD	KVF-H6153EQD
Power supply		V/Ph/Hz	380~415/3/50(60)			
Cooling	Capacity	kW	45.0	50.0	56.0	61.5
		RT	12.8	14.3	16.0	17.6
		kBtu/h	153.5	170.6	191.1	209.8
		kcal/h	38,700	43,000	48,160	52,890
	Power input	kW	12.83	14.47	16.67	18.77
	EER	kW/kW	3.51	3.46	3.36	3.28
Heating	Capacity	kW	50.0	56.0	63.0	69.0
		RT	14.2	16.0	18.0	19.7
		kBtu/h	170.6	191.1	214.9	235.4
		kcal/h	43,000	48,160	54,180	59,340
	Power input	kW	12.47	14.15	15.98	17.86
	COP	kW/kW	4.01	3.96	3.94	3.86
Connectable indoor unit	Total capacity	%	50-130			
	Max. quantity		26	29	33	36
Sound pressure level		dB(A)	60	61	61	61
Pipe connections	Liquid pipe	in.(mm)	Φ1/2(Φ12.7)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)
	Gas pipe	in.(mm)	Φ1-1/8(Φ28.6)	Φ1-1/8(Φ28.6)	Φ1-1/8(Φ28.6)	Φ1-1/8(Φ28.6)
	Oil balance pipe	in.(mm)	Φ5/16(Φ8)			
Fan motor	Type		Axial propeller			
	Quantity		2			
	Air flow rate	m³/h	14,000	16,000	16,000	16,000
		CFM	8,240	9,410	9,410	9,410
	Motor output	W	290+230	420+350	440+350	440+350
	ESP	in.WG(Pa)	0-0.08(0-20)(default)			
		in.WG(Pa)	0.08-0.24(20-60)(customized)			
DC inverter compressor	Quantity		2			
	Capacity	kW	13.8×2	11.8+23.25	23.25×2	23.25×2
		kBtu/h	47.1×2	40.3+79.3	79.3×2	79.3×2
	Crankcase heater	W	27.6×4			
	Oil type		FVC68D			
	Oil charge	gal.(ml)	0.132(500)×2			
Refrigerant	Type		R410A			
	Factory charging	lbs.(kg)	29(13)	29(13)	35(16)	35(16)
Design pressure (High/Low)		MPa	4.4/2.6			
		PSI	640/380			
Net dimension (W×H×D)		inch	52-3/4×64-3/8×31-1/8			
		mm	1340×1635×790			
Packing size (W×H×D)		inch	55-3/8×71-1/16×33-5/8			
		mm	1405×1805×855			
Net weight		lbs.(kg)	655(297)	673(305)	750(340)	750(340)
Gross weight		lbs.(kg)	695(315)	712(323)	790(358)	790(358)
Operating temperature range	Cooling	°F(°C)	23~118.4(-5~48)			
	Heating	°F(°C)	-4~75.2(-20~24)			

Notes:
Capacities are based on the following conditions:
Cooling: Indoor temperature 80.6°F(27°C) DB/66.2°F(19°C) WB; Outdoor temperature 95°F(35°C) DB/75.2°F(24°C) WB.
Heating: Indoor temperature 68°F(20°C) DB/59°F(15°C) WB; Outdoor temperature 44.6°F(7°C) DB/42.8°F(6°C) WB.
Piping length: Interconnecting piping length is 24.6ft.(7.5m), level difference is zero.
Connection piping diameter is based on the condition that the total equivalent liquid length is less than 295.2ft.(90m). When the total equivalent liquid length is more than 295.2ft.(90m), please refer to technical manual to choose the connection piping diameter.
Sound values are measured in a semi-anechoic room, at a position 3.28ft.(1m) in front of the unit and 4.26ft.(1.3m) above the floor.

Outdoor specifications (220V-3Ph-60Hz)

Model			KVF-H2523END	KVF-H2803END	KVF-H3353END	KVF-H4003EMD
Power supply		V/Ph/Hz	220/3/60			
Cooling	Capacity	kW	25.2	28.0	33.5	40.0
		RT	7.2	8.0	9.5	11.4
		kBtu/h	86.0	95.5	114.3	136.5
		kcal/h	21,672	24,080	28,810	34,400
	Power input	kW	5.79	7.02	8.71	10.81
	EER	kW/kW	4.35	3.99	3.85	3.7
Heating	Capacity	kW	27.0	31.5	37.5	45.0
		RT	7.7	9.0	10.7	12.8
		kBtu/h	92.1	107.5	128.0	153.5
		kcal/h	23,220	27,090	32,250	38,700
	Power input	kW	5.79	7.19	8.82	10.98
	COP	kW/kW	4.66	4.38	4.25	4.10
Connectable indoor unit	Total capacity	%	50-130			
	Max. quantity		13	16	20	23
Sound pressure level		dB(A)	57	57	58	60
Pipe connections	Liquid pipe	in.(mm)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)
	Gas pipe	in.(mm)	Φ7/8(Φ22.2)	Φ7/8(Φ22.2)	Φ1(Φ25.4)	Φ1(Φ25.4)
	Oil balance pipe	in.(mm)	Φ5/16(Φ8)			
Fan motor	Type		Axial propeller			
	Quantity		1	1	1	2
	Air flow rate	m³/h	12,000	12,000	12,000	14,000
		CFM	7,060	7,060	7,060	8,240
	Motor output	W	465	465	465	290+230
	ESP	in.WG(Pa)	0-0.08(0-20)(default)			
		in.WG(Pa)	0.08-0.24(20-60)(customized)			
DC inverter compressor	Quantity		1	1	1	2
	Capacity	kW	31.59	31.59	23	13.76×2
		kBtu/h	107.8	107.8	79	47.1×2
	Crankcase heater	W	27.6×2	27.6×2	27.6×2	27.6×4
	Oil type		FVC68D			
	Oil charge	gal.(ml)	0.132(500)	0.132(500)	0.132(500)	0.132(500)×2
Refrigerant	Type		R410A			
	Factory charging	lbs.(kg)	20(9)	20(9)	24(11)	29(13)
Design pressure (High/Low)		MPa	4.4/2.6			
		PSI	640/380			
Net dimension (W×H×D)		inch	39×64-3/8×31-1/8			52-3/4×64-3/8×31-1/8
		mm	990×1635×790			1340×1635×790
Packing size (W×H×D)		inch	41-1/2×71-1/16×33-5/8			55-3/8×71-1/16×33-5/8
		mm	1055×1805×855			1405×1805×855
Net weight		lbs.(kg)	483(219)	483(219)	523(237)	655(297)
Gross weight		lbs.(kg)	516(234)	516(234)	556(252)	695(315)
Operating temperature range	Cooling	°F(°C)	23~118.4(-5~48)			
	Heating	°F(°C)	-4~75.2(-20~24)			

Notes:
Capacities are based on the following conditions:
Cooling: Indoor temperature 80.6°F(27°C) DB/66.2°F(19°C) WB; Outdoor temperature 95°F(35°C) DB/75.2°F(24°C) WB.
Heating: Indoor temperature 68°F(20°C) DB/59°F(15°C) WB; Outdoor temperature 44.6°F(7°C) DB/42.8°F(6°C) WB.
Piping length: Interconnecting piping length is 24.6ft.(7.5m), level difference is zero.
Connection piping diameter is based on the condition that the total equivalent liquid length is less than 295.2ft.(90m). When the total equivalent liquid length is more than 295.2ft.(90m), please refer to technical manual to choose the connection piping diameter.
Sound values are measured in a semi-anechoic room, at a position 3.28ft.(1m) in front of the unit and 4.26ft.(1.3m) above the floor.

Outdoor specifications (220V-3Ph-60Hz)

Model			KVF-H4503END	KVF-H5003END	KVF-H5603END	KVF-H6153END
Power supply		V/Ph/Hz	220/3/60			
Cooling	Capacity	kW	45.0	50.0	56.0	61.5
		RT	12.8	14.3	16.0	17.6
		kBtu/h	153.5	170.6	191.1	209.8
		kcal/h	38,700	43,000	48,160	52,890
	Power input	kW	12.83	14.47	16.67	18.77
	EER	kW/kW	3.51	3.46	3.36	3.28
Heating	Capacity	kW	50.0	56.0	63.0	69.0
		RT	14.2	16.0	18.0	19.7
		kBtu/h	170.6	191.1	214.9	235.4
		kcal/h	43,000	48,160	54,180	59,340
	Power input	kW	12.47	14.15	15.98	17.86
	COP	kW/kW	4.01	3.96	3.94	3.86
Connectable indoor unit	Total capacity	%	50-130			
	Max. quantity		26	29	33	36
Sound pressure level		dB(A)	60	61	61	61
Pipe connections	Liquid pipe	in.(mm)	Φ1/2(Φ12.7)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)
	Gas pipe	in.(mm)	Φ1-1/8(Φ28.6)	Φ1-1/8(Φ28.6)	Φ1-1/8(Φ28.6)	Φ1-1/8(Φ28.6)
	Oil balance pipe	in.(mm)	Φ5/16(Φ8)			
Fan motor	Type		Axial propeller			
	Quantity		2			
	Air flow rate	m³/h	14,000	16,000	16,000	16,000
		CFM	8,240	9,410	9,410	9,410
	Motor output	W	290+230	420+350	440+350	440+350
	ESP	in.WG(Pa)	0-0.08(0-20)(default)			
		in.WG(Pa)	0.08-0.24(20-60)(customized)			
DC inverter compressor	Quantity		2			
	Capacity	kW	13.76×2	31.59+13.76	31.59×2	31.59×2
		kBtu/h	47.1×2	107.8+47.1	107.8×2	107.8×2
	Crankcase heater	W	27.6×4			
	Oil type		FVC68D			
Refrigerant	Oil charge	gal.(ml)	0.132(500)×2			
	Type		R410A			
Factory charging		lbs.(kg)	29(13)	29(13)	35(16)	35(16)
Design pressure (High/Low)		MPa	4.4/2.6			
		PSI	640/380			
Net dimension (W×H×D)		inch	52-3/4×64-3/8×31-1/8			
		mm	1340×1635×790			
Packing size (W×H×D)		inch	55-3/8×71-1/16×33-5/8			
		mm	1405×1805×855			
Net weight		lbs.(kg)	655(297)	673(305)	750(340)	750(340)
Gross weight		lbs.(kg)	695(315)	712(323)	790(358)	790(358)
Operating temperature range	Cooling	°F(°C)	23~118.4(-5~48)			
	Heating	°F(°C)	-4~75.2(-20~24)			

Notes:
Capacities are based on the following conditions:
Cooling: Indoor temperature 80.6°F(27°C) DB/66.2°F(19°C) WB; Outdoor temperature 95°F(35°C) DB/75.2°F(24°C) WB.
Heating: Indoor temperature 68°F(20°C) DB/59°F(15°C) WB; Outdoor temperature 44.6°F(7°C) DB/42.8°F(6°C) WB.
Piping length: Interconnecting piping length is 24.6ft.(7.5m), level difference is zero.
Connection piping diameter is based on the condition that the total equivalent liquid length is less than 295.2ft.(90m). When the total equivalent liquid length is more than 295.2ft.(90m), please refer to technical manual to choose the connection piping diameter.
Sound values are measured in a semi-anechoic room, at a position 3.28ft.(1m) in front of the unit and 4.26ft.(1.3m) above the floor.

Indoor Units Lineup



Indoor Units Lineup

Indoor units lineup

- One-way Cassette
- Two-way Cassette
- Compact Four-way Cassette
- Four-way Cassette
- Low Static Ducted
- Medium Static Ducted
- High Static Ducted
- Ceiling & Floor
- Wall-mounted
- Floor Standing
- Console
- Fresh Air Processing Unit

Type	kW	1.8	2.2	2.8	3.6	4.5	5.6	7.1	8.0	
One-way Cassette										
										
Two-way Cassette										
Compact Four-way Cassette										
Four-way Cassette										
Low Static Ducted										
Meduim Static Ducted										
										
High Static Ducted										
										
										
										
Ceiling & Floor										
Wall-mounted										
										
										
Floor Standing										
Console										
Fresh Air Processing Unit										
										

More than 100 models are available to meet varied customer requirements.

 : Available for 50&60Hz.

 : Only available for 50Hz.


One-way Cassette




- Auto Restart
- Auto Addressing
- Follow Me
- LED Display
- Built-in Drain Pump
- Fresh Air
- Cleanable Panel
- Anti-Cold Air Function

Only 153mm thickness

Compact design, ultra slim body with a minimum thickness of 153mm for model 18-36, especially suitable for narrow ceiling, such as in lobbies and small meeting rooms.




Standard built-in drain pump with 750mm pump head.



Auto swing

Auto swing mechanism guarantees even airflow distribution and a better room temperature balance.




Fresh air, improved air quality

Reserved fresh air intake port for high quality air creates a comfortable and healthy environment.



Special enzyme sterilization and filtering technologies filter bacteria, smog, and pollen. Provide a clean, healthy and natural air supply.



50Hz Specifications

Model			KTV-H183CMD	KTV-H223CMD	KTV-H283CMD	KTV-H363CMD	KTV-H453CMD	KTV-H563CMD	
Power supply			1-phase,220-240V,50Hz						
Cooling capacity		kW	1.8	2.2	2.8	3.6	4.5	5.6	
		kcal/h	1500	1900	2400	3100	3900	4800	
		Btu/h	6100	7500	9600	12300	15400	19100	
Heating capacity		kW	2.2	2.6	3.2	4	5	6.3	
		kcal/h	1900	2200	2800	3400	4300	5400	
		Btu/h	7500	8900	10900	13600	17100	21500	
Rated input	Cooling	W	41	41	41	41	80	85	
	Heating		41	41	41	41	80	85	
Rated current	Cooling	A	0.24	0.24	0.25	0.25	0.37	0.39	
	Heating		0.24	0.24	0.25	0.25	0.37	0.39	
Airflow rate(H/M/L)		m³/h	523/404/275	523/404/275	573/456/315	573/456/315	704/630/503	860/810/702	
		CFM	308/238/162	308/238/162	337/268/185	337/268/185	414/370/296	506/476/413	
Sound pressure level(H/M/L)		dB(A)	37/34/30	38/34/30	39/37/34	40/38/34	41/39/35	42/40/36	
Refrigerant		Type	R410A						
		Control method	EXV						
Indoor Unit	Net dim.(W×H×D)	mm	1054×169×425				1147×200×640		
	Gross dim.(W×H×D)		1155×245×490				1380×265×775		
	Net/Gross weight	kg	12.5/16			13/16.5		31.5/37.2	
Panel	Net dim.(W×H×D)	mm	1180×36.5×465			1180×36.5×465		1425×10×755	
	Gross dim.(W×H×D)		1232×107×517			1232×107×517		1500×110×870	
	Net/Gross weight	kg	3.5/5.2			3.5/5.2		9/12	
Piping connections	L(flare)	mm	Φ6.35			Φ6.35		Φ6.35	Φ9.53
	G(flare)	mm	Φ12.7			Φ12.7		Φ12.7	Φ15.9
	Drain piping	mm	OD Φ25			OD Φ25		OD Φ25	
Standard controller			Wireless remote controller RM05/BG(T)E-A/E)						

60Hz Specifications

Model			KTV-H183CND	KTV-H223CND	KTV-H283CND	KTV-H363CND	KTV-H453CND	KTV-H563CND	
Power supply			1-phase,208-230V,60Hz				1-phase,220-240V,60Hz		
Cooling capacity		kW	1.8	2.2	2.8	3.6	4.5	5.6	
		kcal/h	1500	1900	2400	3100	3900	4800	
		Btu/h	6100	7500	9600	12300	15400	19100	
Heating capacity		kW	2.2	2.6	3.2	4	5	6.3	
		kcal/h	1900	2200	2800	3400	4300	5400	
		Btu/h	7500	8900	10900	13600	17100	21500	
Rated input	Cooling	W	41	41	41	41	80	85	
	Heating		41	41	41	41	80	85	
Rated current	Cooling	A	0.24	0.24	0.25	0.25	0.37	0.39	
	Heating		0.24	0.24	0.25	0.25	0.37	0.39	
Airflow rate (H/M/L)		m³/h	523/404/275	523/404/275	573/456/315	573/456/315	704/630/503	860/810/702	
		CFM	308/238/162	308/238/162	337/268/185	337/268/185	414/370/296	506/476/413	
Sound pressure level(H/M/L)		dB(A)	37/34/30	38/34/30	39/37/34	40/38/34	41/39/35	42/40/36	
Refrigerant		Type	R410A						
		Control method	EXV						
Indoor Unit	Net dim.(W×H×D)	in.(mm)	41-1/2×6-21/32×16-47/64(1054×169×425)				45-5/32×7-7/8×25-13/64 (1147×200×640)		
	Gross dim.(W×H×D)		45-15/32×9-41/64×19-19/64(1155×245×490)				54-21/64×10-7/16×30-33/64 (1380×265×775)		
	Net/Gross weight	lbs.(kg)	27.8/35.3(12.5/16)			28.8/36.4(13/16.5)		(69.5/82.1)31.5/37.2	
Panel	Net dim.(W×H×D)	in.(mm)	46-29/64×1-7/16×18-5/16 (1180×36.5×465)			46-29/64×1-7/16×18-5/16 (1180×36.5×465)		56-7/64×25/64×29-23/32 (1425×10×755)	
	Gross dim.(W×H×D)		48-1/2×4-7/32×20-23/64 (1232×107×517)			48-1/2×4-7/32×20-23/64 (1232×107×517)		59-1/16×4-21/64×34-1/4 (1500×110×870)	
	Net/Gross weight	lbs.(kg)	7.7/11.5(3.5/5.2)			7.7/11.5(3.5/5.2)		19.6/26.5(9/12)	
Piping connections	L(flare)	in.(mm)	1/4 (Φ6.35)			1/4(Φ6.35)		1/4(Φ6.35)	3/8(Φ9.53)
	G(flare)	in.(mm)	1/2(Φ12.7)			1/2(Φ12.7)		1/2(Φ12.7)	5/8(Φ15.9)
	Drain piping	in.(mm)	OD 63/64(Φ25)			OD 63/64(Φ25)		OD 63/64(Φ25)	
Standard controller			Wireless remote controller (RM05/BG(T)E-A)						

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temp. : 80.6°F(27°C)DB,66.2°F(19°C)WB,and outdoor temp.: 95°F(35°C)DB,equivalent ref. piping: 26.25ft. (8m) (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temp.: 68°F(20°C)DB, outdoor temp.: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft. (8m) (horizontal)

3. Sound Level is measured 4.59ft.(1.4m) below the unit

Indoor units lineup

Two-way Cassette




- Auto Restart
- Fresh Air
- Auto Addressing
- Cleanable Panel
- Follow Me
- Anti-Cold Air Function
- LED Display
- Built-in Drain Pump

Quiet operation


Optimized airflow duct with low resistance greatly reduces noise, minimum down to 24dB(A).

Stylish design and slim body

Thanks to the stylish appearance and slim body, the unit suits any room's decor and ambience. At only 300mm high, the unit requires only a small suspended ceiling space. Installation has no height limitations, which makes overall design features much more flexible.



Standard built-in drain pump with 750mm pump head (higher pump head can be customized).



Flat-type suction grille design greatly simplifies maintenance work.

High airflow

High airflow for high ceiling application guarantees comfort in large space. It makes every person in the room get even distribution of airflow and temperature.



50Hz Specifications

Model		KTV-H223DMD	KTV-H283DMD	KTV-H363DMD	KTV-H453DMD	KTV-H563DMD	KTV-H713DMD
Power supply		1-phase, 220-240V, 50Hz					
Cooling capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
	kcal/h	1,900	2,400	3,100	3,900	4,800	6,100
	Btu/h	7,500	9,600	12,300	15,400	19,100	24,200
Heating capacity	kW	2.6	3.2	4.0	5.0	6.3	8.0
	kcal/h	2,200	2,800	3,400	4,300	5,400	6,900
	Btu/h	8,900	10,900	13,600	17,100	21,500	27,300
Power input	Cooling	W	57	57	60	92	154
	Heating		57	57	60	92	154
Rated current	Cooling	A	0.35	0.45	0.45	0.55	0.75
	Heating		0.35	0.45	0.45	0.55	0.75
Airflow rate(H/M/L)		m³/h	654/530/410	654/530/410	725/591/458	850/670/550	980/800/670
		CFM	385/312/241	385/312/241	427/348/270	500/394/324	577/471/394
Sound pressure level(H/M/L)		dB(A)	33/29/24	36/32/29	36/32/29	39/35/30	39/35/30
Refrigerant		Type	R410A				
		Control method	EXV				
Body	Net dim.(W×H×D)	mm	1,172×299×591	1,172×299×591	1,172×299×591	1,172×299×591	1,172×299×591
	Gross dim.(W×H×D)		1,355×400×675	1,355×400×675	1,355×400×675	1,355×400×675	1,355×400×675
	Net/gross weight	kg	34/42.5	34/42.5	34/42.5	36.5/45	36.5/45
Panel	Net dim.(W×H×D)	mm	1,430×53×680	1,430×53×680	1,430×53×680	1,430×53×680	1,430×53×680
	Gross dim.(W×H×D)		1,525×130×765	1,525×130×765	1,525×130×765	1,525×130×765	1,525×130×765
	Net/gross weight	kg	10.5/15	10.5/15	10.5/15	10.5/15	10.5/15
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9
	Drain piping	mm	OD Φ32	OD Φ32	OD Φ32	OD Φ32	OD Φ32
Standard controller		-	Wireless remote controller(RM05/BG(T)E-A)				

60Hz Specifications

Model		KTV-H223DND	KTV-H283DND	KTV-H363DND	KTV-H453DND	KTV-H563DND	KTV-H713DND
Power supply		1-phase, 208-230V, 60Hz					
Cooling capacity	kW	2.2	2.8	3.6	4.5	5.6	7.1
	kcal/h	1,900	2,400	3,100	3,900	4,800	6,100
	Btu/h	7,500	9600	12,300	15,400	19,100	24,200
Heating capacity	kW	2.6	3.2	4	5	6.3	8
	kcal/h	2200	2,800	3,400	4,300	5,400	6,900
	Btu/h	8,900	10,900	13,600	17,100	21,500	27,300
Power input	Cooling	W	78	78	83	115	133
	Heating		78	78	83	115	133
Rated current	Cooling	A	0.35	0.45	0.45	0.55	0.55
	Heating		0.35	0.45	0.45	0.55	0.55
Airflow rate(H/M/L)		m³/h	674/509/381	674/509/381	740/577/435	878/689/561	941/776/654
		CFM	397/300/224	397/300/224	436/340/256	517/406/330	554/457/385
Sound pressure level(H/M/L)		dB(A)	33/29/24	36/32/29	36/32/29	39/35/30	39/35/30
Refrigerant		Type	R410A				
		Control method	EXV				
Body	Net dim.(W×H×D)	in.(mm)	46-9/32×11-49/64×23-17/64(1172×299×591)				
	Gross dim.(W×H×D)		53-11/32×15-3/4×26-37/64(1355×400×675)				
	Net/gross weight	lbs.(kg)	75/94(34/42.5)	75/94(34/42.5)	75/94(34/42.5)	80.5/99(36.5/45)	80.5/99(36.5/45)
Panel	Net dim.(W×H×D)	in.(mm)	56-19/64×2-3/32×26-49/64(1430×53×680)				
	Gross dim.(W×H×D)		60-3/64×5-1/8×30-1/8(1525×130×765)				
	Net/gross weight	lbs.(kg)	23/33(10.5/15)	23/33(10.5/15)	23/33(10.5/15)	23/33(10.5/15)	23/33(10.5/15)
Piping connections	L(flare)	in.(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)	Φ3/8(9.53)	Φ3/8(9.53)
	G(flare)	in.(mm)	Φ1/2(12.7)	Φ1/2(12.7)	Φ1/2(12.7)	Φ5/8(15.9)	Φ5/8(15.9)
	Drain piping	in.(mm)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)				

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temp. : 80.6°F(27°C)DB,66.2°F(19°C)WB,and outdoor temp.: 95°F(35°C)DB,equivalent ref. piping: 26.25ft. (8m) (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temp.: 68°F(20°C)DB, outdoor temp.: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft. (8m) (horizontal)

3. Sound Level is measured 4.59ft. (1.4m) below the unit


Indoor units lineup

Compact Four-way Cassette



- Auto Restart
- Auto Addressing
- Follow Me
- Built-in Drain Pump
- Super High Air Flow
- Fresh Air
- Cleanable Panel
- Anti-Cold Air Function
- LED Display

Compact design, easy installation




Extremely compact casing suits any room's decor and requires little space for installation on a low ceiling. Due to the compact body and light weight, all models can be installed without a hoist.

Fresh air intake




Fresh air can enter through the cassette unit so you can enjoy even fresher air in your room.

Quiet operation, gentle air supply



Streamline plate ensures quiet operation. Advanced 3-D spiral fan design reduces air resistance and operation noise.

Sub duct




Sub duct enables you to use the same air conditioner unit to cool an additional smaller space nearby.

360° Airflow outlet



360° air outlet provides strong air flow circulation to cool or heat every corner of a room and evenly distribute temperature.

High-lift drain pump



Drain pump with a 500mm pump head is fitted as standard; maximum 600mm pump head is available.

50Hz Specifications

Model			KTV-H153AMD	KTV-H223AMD	KTV-H283AMD	KTV-H363AMD	KTV-H453AMD
Power supply			1-phase,220-240V,50Hz				
Cooling capacity		kW	1.5	2.2	2.8	3.6	4.5
		kcal/h	1300	1900	2400	3100	3900
		Btu/h	5100	7500	9600	12300	15400
Heating capacity		kW	1.7	2.4	3.2	4	5
		kcal/h	1500	2100	2700	3400	4300
		Btu/h	5800	8200	10900	13600	17100
Rated input	Cooling	W	36	50	50	56	56
	Heating		36	50	50	56	56
Rated current	Cooling	A	0.22	0.22	0.22	0.25	0.25
	Heating		0.22	0.22	0.22	0.25	0.25
Airflow rate(SH/H/M/L)		m³/h	501/435/283/208	522/414/313/238	522/414/313/238	610/521/409/314	610/521/409/314
		CFM	295/256/167/98	307/244/184/140	307/244/184/140	359/307/241/185	359/307/241/185
Sound pressure level(H/M/L)		dB(A)	34.9/32.5/22.5	35.8/33.4/23.4	35.8/33.4/23.4	41.5/35.6/28.8	41.5/35.6/28.8
Refrigerant		Type	R410A				
		Control method	EXV				
Indoor Unit	Net dim.(W×H×D)	mm	570x260x570	570x260x570	570x260x570	570x260x570	570x260x570
	Gross dim.(W×H×D)		675x285x675	675x285x675	675x285x675	675x285x675	675x285x675
	Net/Gross weight	kg	16/19.5	16/20	16/20	18/22	18/22
Panel	Net dim.(W×H×D)	mm	647x50x647	647x50x647	647x50x647	647x50x647	647x50x647
	Gross dim.(W×H×D)		715x123x715	715x123x715	715x123x715	715x123x715	715x123x715
	Net/Gross weight	kg	2.4/4.5	2.4/4.5	2.4/4.5	2.4/4.5	2.4/4.5
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ12.7
	Drain piping	mm	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25
Standard controller			Wireless remote controller (RM05/BG(T)E-A)				

60Hz Specifications

Model			KTV-H223AND	KTV-H283AND	KTV-H363AND	KTV-H453AND
Power supply			1-phase, 208-230V 60Hz			
Cooling capacity		kW	2.2	2.8	3.6	4.5
		kcal/h	1,900	2,400	3,100	3,900
		Btu/h	7,500	9,600	12,300	15,400
Heating capacity		kW	2.4	3.2	4	5
		kcal/h	2,100	2,800	3,400	4,300
		Btu/h	8,200	10,900	13,600	17,100
Power input	Cooling	W	51	52	58	58
	Heating		43	44	50	51
Rated current	Cooling	A	0.175	0.175	0.21	0.21
	Heating		0.175	0.175	0.21	0.21
Airflow rate(SH/H/M/L)		m³/h	532/397/292/215	539/408/310/231	632/496/359/263	632/496/359/263
		CFM	313/234/172/127	317/240/182/136	372/292/211/155	372/292/211/155
Sound pressure level(H/M/L)		dB(A)	35.8/33.4/23.4	35.8/33.4/23.4	41.5/35.6/28.8	41.5/35.6/28.8
Refrigerant		Type	R410A			
		Control method	EXV			
Body	Net dim.(W×H×D)	in.(mm)	22-7/16×10-15/64×22-7/16(570×260×570)			
	Gross dim.(W×H×D)		26-9/16×11-7/32×26-9/16(675×285×675)			
	Net/Gross weight	lbs.(kg)	35.3/44.1/(16/20)	35.3/44.1/(16/20)	39.7/48.5(18/22)	39.7/48.5(18/22)
Panel	Net dim.(W×H×D)	in.(mm)	25-15/32×1-31/32×25-15/2(647×50×647)			
	Gross dim.(W×H×D)		28-5/32×4-27/32×28-5/32 (715×123×715)			
	Net/Gross weight	lbs.(kg)	6.6/11(3/5)	6.6/11(3/5)	6.6/11(3/5)	6.6/11(3/5)
Piping connections	L(flare)	in.(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)
	G(flare)	in.(mm)	Φ1/2(12.7)	Φ1/2(12.7)	Φ1/2(12.7)	Φ1/2(12.7)
	Drain piping	in.(mm)	OD 63/64(Φ25)	OD 63/64(Φ25)	OD 63/64(Φ25)	OD 63/64(Φ25)
Standard controller			Wireless remote controller (RM05/BG(T)E-A)			

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temp. : 80.6°F(27°C)DB,66.2°F(19°C)WB, and outdoor temp.: 95°F(35°C)DB,equivalent ref. piping: 26.25ft. (8m) (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temp.: 68°F(20°C)DB, outdoor temp.: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft. (8m) (horizontal)

3. Sound Level is measured 4.59ft. (1.4m) below the unit

Indoor units lineup

Four-way Cassette



- | | |
|---|--|
|  Auto Restart |  Fresh Air |
|  Auto Addressing |  Cleanable Panel |
|  Follow Me |  Anti-Cold Air Function |
|  Built-in Drain Pump |  LED Display |
|  Super High Air Flow | |

Quiet operation, gentle air supply

- Streamline plate ensures quiet operation.
- Advanced 3-D spiral fan design reduces air resistance and operation noise.



Diffuser


3-D spiral fan blade

Fresh air intake



Fresh air can enter through the cassette unit so you can enjoy even fresher air in your room.

Sub duct




Sub duct enables you to use the same air conditioner unit to cool an additional smaller space nearby.

Easy troubleshooting

By adding digital tube on the display board, Error Codes can be displayed directly for troubleshooting.




Four-way uniform airflow



Four air discharge ports provide strong air flow circulation to cool or heat every corner of a room and evenly distribute temperature. High airflow mode can maximize the conditioning effect in rooms that are over 3m high.

High-lift drain pump

Drain pump can take condenser water up to 750mm, which simplifies installation of the drain piping system.



50Hz Specifications

Model			KTV-H283BMD	KTV-H363BMD	KTV-H453BMD	KTV-H563BMD	KTV-H713BMD
Power supply			1-phase, 220-240V, 50Hz				
Cooling capacity		kW	2.8	3.6	4.5	5.6	7.1
		kcal/h	2,400	3,100	3,900	4,800	6,100
		Btu/h	9,600	12,300	15,400	19,100	24,200
Heating capacity		kW	3.2	4.0	5.0	6.3	8.0
		kcal/h	2,800	3,400	4,300	5,400	6,900
		Btu/h	10,900	13,600	17,100	21,500	27,300
Power input	Cooling	W	65	65	75	75	82
	Heating		65	65	75	75	82
Rated current	Cooling	A	0.4	0.4	0.4	0.4	0.5
	Heating		0.4	0.4	0.4	0.4	0.5
Airflow rate(SH/H/M/L)		m³/h	1,187/847/766/640	1,187/847/766/640	1,121/864/755/658	1,121/864/755/658	1,385/1,157/955/749
		CFM	699/498/450/376	699/498/450/376	660/508/444/387	660/508/444/387	815/680/562/440
Sound pressure level(H/M/L)		dB(A)	42/38/35	42/38/35	42/38/35	42/38/35	45/42/39
Refrigerant		Type	R410A				
		Control method	EXV				
Body	Net dim.(W×H×D)	mm	904×230×840	904×230×840	904×230×840	904×230×840	904×230×840
	Gross dim.(W×H×D)		955×260×955	955×260×955	955×260×955	955×260×955	955×260×955
	Net/gross weight	kg	24/28	24/28	26/30	26/30	26/30
Panel	Net dim.(W×H×D)	mm	950×54.5×950	950×54.5×950	950×54.5×950	950×54.5×950	950×54.5×950
	Gross dim.(W×H×D)		1,035×90×1,035	1,035×90×1,035	1,035×90×1,035	1,035×90×1,035	1,035×90×1,035
	Net/gross weight	kg	6/9	6/9	6/9	6/9	6/9
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.53	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9
	Drain piping	mm	OD Φ32	OD Φ32	OD Φ32	OD Φ32	OD Φ32
Standard controller		-	Wireless remote controller(RM05/BG(T)E-A)				

Model			KTV-H803BMD	KTV-H903BMD	KTV-H1003BMD	KTV-H1123BMD	KTV-H1403BMD
Power supply			1-phase, 220-240V, 50Hz				
Cooling capacity		kW	8.0	9.0	10.0	11.2	14.0
		kcal/h	6,900	7,700	8,600	9,600	12,000
		Btu/h	27,300	30,700	34,100	38,200	47,800
Heating capacity		kW	9.0	10.0	11.1	12.5	15.0
		kcal/h	7,700	8,600	9,500	10,800	12,900
		Btu/h	30,700	34,100	37,900	42,700	51,200
Power input	Cooling	W	97	160	160	160	170
	Heating		97	160	160	160	170
Rated current	Cooling	A	0.5	0.7	0.7	0.7	0.8
	Heating		0.5	0.7	0.7	0.7	0.8
Airflow rate(SH/H/M/L)		m³/h	1,431/1,236/973/729	1,758/1,540/1,300/1,120	1,758/1,540/1,300/1,120	1,758/1,540/1,300/1,120	1,843/1,800/1,500/1,280
		CFM	842/727/572/429	1,035/906/765/659	1,035/906/765/659	1,035/906/765/659	1,085/1,059/883/753
Sound pressure level(H/M/L)		dB(A)	45/42/39	48/45/43	48/45/43	48/45/43	50/47/44
Refrigerant		Type	R410A				
		Control method	EXV				
Body	Net dim.(W×H×D)	mm	904×230×840	904×300×840	904×300×840	904×300×840	904×300×840
	Gross dim.(W×H×D)		955×260×955	955×330×955	955×330×955	955×330×955	955×330×955
	Net/gross weight	kg	26/30	32/37	32/37	32/37	32/37
Panel	Net dim.(W×H×D)	mm	950×54.5×950	950×54.5×950	950×54.5×950	950×54.5×950	950×54.5×950
	Gross dim.(W×H×D)		1,035×90×1,035	1,035×90×1,035	1,035×90×1,035	1,035×90×1,035	1,035×90×1,035
	Net/gross weight	kg	6/9	6/9	6/9	6/9	6/9
Piping connections	L(flare)	mm	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	OD Φ32	OD Φ32	OD Φ32	OD Φ32	OD Φ32
Standard controller		-	Wireless remote controller(RM05/BG(T)E-A)				

- Notes:
- 1. Nominal cooling capacities are based on the following conditions: return air temperature. : 27°CDB,19°CWB,outdoor temperature.:35°CDB, equivalent ref. Piping: 8m(horizontal)
 - 2. Nominal heating capacities are based on the following conditions: return air temperature.: 20°CDB,outdoor temperature.: 7°CDB, 6°CWB, equivalent ref. Piping: 8m(horizontal)
 - 3. Sound level is measured at 1.4m below the unit.

Indoor units lineup

60Hz Specifications

Model			KTV-H283BND	KTV-H363BND	KTV-H453BND	KTV-H563BND	KTV-H713BND
Power supply			1-phase, 220-240V, 60Hz				
Cooling capacity		kW	2.8	3.6	4.5	5.6	7.1
		kcal/h	2,400	3,100	3,900	4,800	6,100
		Btu/h	9,600	12,300	15,400	19,100	24,200
Heating capacity		kW	3.2	4	5	6.3	8
		kcal/h	2,800	3,400	4,300	5,400	6,900
		Btu/h	10,900	13,600	17,100	21,500	27,300
Power input	Cooling	W	90	90	90	90	115
	Heating		90	90	90	90	115
Rated current	Cooling	A	0.4	0.4	0.4	0.4	0.5
	Heating		0.4	0.4	0.4	0.4	0.5
Airflow rate(SH/H/M/L)		m³/h	1,155/847/766/640	1,155/847/766/640	1,207/864/755/658	1,207/864/755/658	1,327/1,157/955/749
		CFM	680/499/451/377	680/499/451/377	710/509/444/387	710/509/444/387	781/681/562/441
Sound pressure level(H/M/L)		dB(A)	42/38/35	42/38/35	42/38/35	42/38/35	45/42/39
Refrigerant		Type	R410A				
		Control method	EXV				
Body	Net dim.(W×H×D)	in.(mm)	35-19/32×9-1/16×33-5/64(904×230×840)				
	Gross dim.(W×H×D)		37-19/32×10-15/64×37-19/32(955×260×955)				
	Net/gross weight		53 /61.7(24/28)	53 /61.7(24/28)	57.3 /66.2(26/30)	57.3 /66.2(26/30)	57.3 /66.2(26/30)
Panel	Net dim.(W×H×D)	in.(mm)	37-13/32×2-9/64×37-13/32(950×54.5×950)				
	Gross dim.(W×H×D)		40-3/4×3-35/64×40-3/4(1,035×90×1,035)				
	Net/gross weight		11.0/19.9(5/9)	11.0/19.9(5/9)	11.0/19.9(5/9)	11.0/19.9(5/9)	11.0/19.9(5/9)
Piping connections	L(flare)	in.(mm)	Φ1/4(6.35)	Φ1/4(6.35)	Φ1/4(6.35)	Φ3/8(9.53)	Φ3/8(9.53)
	G(flare)	in.(mm)	Φ1/2(12.7)	Φ1/2(12.7)	Φ1/2(12.7)	Φ5/8(15.9)	Φ5/8(15.9)
	Drain piping	in.(mm)	OD 1-17/64(Φ32)				
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)				

Model			KTV-H803BND	KTV-H903BND	KTV-H1003BND	KTV-H1123BND	KTV-H1403BND
Power supply			1-phase, 220-240V, 60Hz				
Cooling capacity		kW	8	9	10	11.2	14
		kcal/h	6,900	7,700	8,600	9,600	12,000
		Btu/h	27,300	30,700	34,100	38,200	47,800
Heating capacity		kW	9	10	11.1	12.5	15
		kcal/h	7,700	8,600	9,500	10,800	12,900
		Btu/h	30,700	34,100	37,900	42,700	51,200
Power input	Cooling	W	115	160	160	160	180
	Heating		115	160	160	160	180
Rated current	Cooling	A	0.5	0.7	0.7	0.7	0.8
	Heating		0.5	0.7	0.7	0.7	0.8
Airflow rate(SH/H/M/L)		m³/h	1,357/1,236/973/729	1,795/1,590/1,300/1,090	1,795/1,590/1,300/1,090	1,795/1,590/1,300/1,090	1,881/1,678/1,358/1,115
		CFM	799/727/573/429	1,057/936/765/642	1,057/936/765/642	1,057/936/765/642	1,107/988/799/656
Sound pressure level(H/M/L)		dB(A)	45/42/39	48/45/43	48/45/43	48/45/43	50/47/44
Refrigerant		Type	R410A				
		Control method	EXV				
Body	Net dim.(W×H×D)	in.(mm)	35-19/32×9-1/16×33-5/64(904×230×840)	35-19/32×11-13/16×33-5/64(904×300×840)			
	Gross dim.(W×H×D)		37-19/32×10-15/64×37-19/32(955×260×955)	37-19/32×11-13/16×37-19/32(955×330×955)			
	Net/gross weight		57.3/66(26/30)	70.5/81.6(32/37)	70.5/81.6(32/37)	70.5/81.6(32/37)	70.5/81.6(32/37)
Panel	Net dim.(W×H×D)	in.(mm)	37-13/32×2-9/64×37-13/32(950×54.5×950)				
	Gross dim.(W×H×D)		40-3/4×3-35/64×40-3/4(1,035×90×1,035)				
	Net/gross weight		11.0/17.6(5/8)	11.0/17.6(5/8)	11.0/17.6(5/8)	11.0/17.6(5/8)	11.0/17.6(5/8)
Piping connections	L(flare)	in.(mm)	Φ3/8(9.53)	Φ3/8(9.53)	Φ3/8(9.53)	Φ3/8(9.53)	Φ3/8(9.53)
	G(flare)	in.(mm)	Φ5/8(15.9)	Φ5/8(15.9)	Φ5/8(15.9)	Φ5/8(15.9)	Φ5/8(15.9)
	Drain piping	in.(mm)	OD 1-17/64(Φ32)				
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)				

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temperature : 80.6°F(27°C)DB,66.2°F(19°C)WB, and outdoor temperature: 95°F(35°C)DB,equivalent ref. piping: 26.25ft. (8m) (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temperature: 68°F(20°C)DB,outdoor temperature: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft. (8m) (horizontal)

3. Sound Level is measured 4.59ft. (1.4m) below the unit

Low Static Ducted



Auto Restart



Anti-Cold Air Function



Auto Addressing



Super High Air Flow



Follow Me



Wireless Remote Controller

Low sound level



Utilizes the centrifugal type blower, provides a minimum noise level of 24dB (A), an excellent choice for hotels and other sound-sensitive places.


V shape evaporator-- good for heat exchanging

V shape evaporator design enhances heat exchanging efficiency about 22%.

Convenient for installation and maintenance


The EXV is fixed inside the indoor unit.

Compact design



Uniform 210mm in height, compact design for easy locate where space ceiling is limited, The whole body adopts fireproof plastic material, the minimum weight is 14kg.

Options



A drain pump with 750mm pumphead is an optional accessory.

50Hz Specifications

Model			KLV-H183AMD	KLV-H223AMD	KLV-H283AMD	KLV-H363AMD	KLV-H453AMD	KLV-H563AMD	KLV-H713AMD
Power supply			220-240V~1Ph~50Hz						
Cooling capacity		kW	1.8	2.2	2.8	3.6	4.5	5.6	7.1
		kcal/h	1500	1900	2400	3100	3900	4800	6100
		Btu/h	6100	7500	9600	12300	15400	19100	24200
Heating capacity		kW	2.2	2.6	3.2	4	5	6.3	8
		kcal/h	1900	2200	2800	3400	4300	5400	6900
		Btu/h	7500	8900	10900	13600	17100	21500	27300
Rated input	Cooling	W	59	59	59	65	105	105	130
	Heating		59	59	59	65	105	105	130
Rated current	Cooling	A	0.31	0.31	0.31	0.36	0.36	0.36	0.5
	Heating		0.31	0.31	0.31	0.36	0.36	0.36	0.5
Airflow rate(SH/H/M/L)		m³/h	606(30pa)/578/512/409			646(30pa) /617/551/441	803(30Pa)/824/690/609		1207(30pa) /1060/970/811
		CFM	357/340/301/241			380/363/324/260	473/485/406/358		710/624/571/477
External Static Pressure		Pa	10(10~30)	10(10~30)	10(10~30)	10(10~30)	10(10~30)	10(10~30)	10(10~30)
Sound pressure level (H/M/L)		dB(A)	35/27/24	35/27/24	35/27/24	38/32/28	39/32/29	39/32/29	41/33/30
Refrigerant type		Type	R410A	R410A	R410A	R410A	R410A	R410A	R410A
		Control type	EXV	EXV	EXV	EXV	EXV	EXV	EXV
Indoor unit	Dimension (W×H×D)	mm	740×210×470	740×210×470	740×210×470	740×210×470	960×210×470	960×210×470	1180×210×470
	Packing (W×H×D)	mm	910×230×510	910×230×510	910×230×510	910×230×510	1130×230×510	1130×230×510	1350×230×510
	Net/Gross weight	kg	14/17.5	14/17.5	14/17.5	14/17.5	17.5/22	17.5/22	21/26.5
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9
	Drain piping	mm	Φ25	Φ25	Φ25	Φ25	Φ25	Φ25	Φ25
Standard controller			Wireless remote controller (RM05/BG(T)E-A)						


60Hz Specifications

Model			KLV-H183AMD	KLV-H223AMD	KLV-H283AMD	KLV-H363AMD	KLV-H453AMD	KLV-H563AMD	KLV-H713AMD
Power supply			208-230V~1Ph~60Hz	208-230V~1Ph~60Hz	208-230V~1Ph~60Hz	208-230V~1Ph~60Hz	208-230V~1Ph~60Hz	208-230V~1Ph~60Hz	208-230V~1Ph~60Hz
Cooling capacity		kW	1.8	2.2	2.8	3.6	4.5	5.6	7.1
		kcal/h	1500	1900	2400	3100	3900	4800	6100
		Btu/h	6100	7500	9600	12300	15400	19100	24200
Heating capacity		kW	2.2	2.6	3.2	4	5	6.3	8
		kcal/h	1900	2200	2800	3400	4300	5400	6900
		Btu/h	7500	8900	10900	13600	17100	21500	27300
Rated input	Cooling	W	59	59	59	65	105	105	130
	Heating		59	59	59	65	105	105	130
Rated current	Cooling	A	0.26	0.26	0.26	0.3	0.5	0.5	0.6
	Heating		0.26	0.26	0.26	0.3	0.5	0.5	0.6
Airflow rate(SH/H/M/L)		m³/h	606(30pa)/578/512/409	606(30pa)/578/512/409	606(30pa)/578/512/409	646(30pa)/617/551/441	803(30pa)/824/690/609	803(30pa)/824/690/609	1207(30pa)/1060/970/811
		CFM	357/340/301/241	357/340/301/241	357/340/301/241	380/363/324/260	473/485/406/358	473/485/406/358	710/624/571/477
External Static Pressure		Pa	10(10~30)	10(10~30)	10(10~30)	10(10~30)	10(10~30)	10(10~30)	10(10~30)
		Sound pressure level (H/M/L)	dB(A)	35/27/24	35/27/24	35/27/24	38/32/28	39/32/29	39/32/29
Refrigerant type		Type	R410A	R410A	R410A	R410A	R410A	R410A	R410A
		Control type	EXV	EXV	EXV	EXV	EXV	EXV	EXV
Indoor unit	Dimension (W×H×D)	in.(mm)	29-9/64×8-17/64×18-1/2(740×210×470)				37-51/64×8-17/64×18-1/2(960×210×470)		46-29/64×8-17/64×18-1/2(1180×210×470)
	Packing (W×H×D)	in.(mm)	35-53/64×9-1/16×20-5/64(910×230×510)				44-31/64×9-1/16×20-5/64(1130×230×510)		53-5/32×9-1/16×20-5/64(1350×230×510)
	Net/Gross/weight	lbs.(kg)	32.0/39.7(14.5/18)				39.7/49.6(18/22.5)	39.7/49.6(18/22.5)	49.6/58.5(22.5/26.5)
Piping connections	L(flare)	in.(mm)	1/4(Φ6.35)	1/4(Φ6.35)	1/4(Φ6.35)	1/4(Φ6.35)	1/4(Φ6.35)	3/8(Φ9.53)	3/8(Φ9.53)
	G(flare)	in.(mm)	1/2(Φ12.7)	1/2(Φ12.7)	1/2(Φ12.7)	1/2(Φ12.7)	Φ12.7	5/8(Φ15.9)	5/8(Φ15.9)
	Drain piping	in.(mm)	OD 63/64(Φ25)						
Standard controller			Wireless remote controller (RM05/BG(T)E-A)						

- Notes:
- Nominal cooling capacities are based on the following conditions: return air temp.: 27°CDB, 19°CWB, and outdoor temp.:35°CDB, equivalent ref. piping: 8m (horizontal)
 - Nominal heating capacities are based on the following conditions: return air temp.: 20°CDB, outdoor temp.: 7°CDB, 6°CWB, and equivalent ref. Piping: 8m (horizontal)
 - Sound level is measured at 1.4m below the air outlet.
- * External static pressure is based on high speed indoor air flow.


Indoor units lineup

Medium Static Ducted



- Auto Restart
- Follow Me
- Built-in Drain Pump
- Auto Addressing
- Connectable To Duct
- Fresh Air
- Anti-Cold Air Function
- Wired Controller
- Super High Air Flow

Compact size



Only 210mm (15~71 models) or 270mm (80 to 112 models) or 300mm (140 model) in height.

External static pressure

Four speed fan motor (Super high speed is optional)

Change the wiring connection from 'SH' to 'H' to change the ESP.

Convenient installation




The EXV is fixed inside of the indoor unit.

Standard filter is housed in an aluminum frame, which is removable from the bottom in the downward direction.

Suction chamber is included as standard equipment.

Fresh air hole, air inlet/outlet flange are standard for easy duct connection.

A rear air inlet is standard and an inlet at the bottom is optional. Both use the same connectable duct.



Flexible control and easy maintenance

Standard wired remote controller KJR-29B1/BK-E.

The electrical control box can be removed 1m away from the unit for easy maintenance access. Customers need to request this service in advance for it is done at Koolman CAC factory.

Standard functional ports are included such as Remote On/Off Dry contact switch and Alarm signal output (220V).

50Hz Specifications

Model			KMV-H15 3AMD	KMV-H22 3AMD	KMV-H28 3AMD	KMV-H36 3AMD	KMV-H45 3AMD	KMV-H56 3AMD
Power supply			1-phase,220-240V,50Hz					
Cooling capacity		kW	1.5	2.2	2.8	3.6	4.5	5.6
		kcal/h	1290	1900	2400	3100	3900	4800
		Btu/h	5100	7500	9600	12300	15400	19100
Heating capacity		kW	1.7	2.6	3.2	4	5	6.3
		kcal/h	1500	2200	2800	3400	4300	5400
		Btu/h	5800	8900	10900	13600	17100	21500
Rated input	Cooling	W	56	57	57	61	98	103
	Heating		56	57	57	61	98	103
Rated current	Cooling	A	0.31	0.31	0.31	0.33	0.36	0.36
	Heating		0.31	0.31	0.31	0.33	0.36	0.36
Airflow rate(SH/H/ML)		m ³ /h	588(30pa)/538/456/375			614(30pa)/597/514/429	763(30pa)/811/684/575	763(30pa)/811/684/575
		CFM	346/317/268/221			361/351/303/253	449/477/403/338	449/477/403/338
ESP(external static pressure)		Pa	10(10-30)	10(10-30)	10(10-30)	10(10-30)	10(10-30)	10(10-30)
Sound pressure level(H/M/L)		dB(A)	35.8/34.6/31.4	36/35/32	37/35/32	38.6/37.5/33.8	39/37.9/34	39/37.9/34
Refrigerant		Type	R410A					
		Control method	EXV					
Indoor Unit	Net dim.(W×H×D)	mm	740x210x500	740x210x500	740x210x500	740x210x500	960x210x500	960x210x500
	Gross dim.(V×H×D)		870×285×525	870×285×525	870×285×525	870×285×525	1,115x285x525	1,115x285x525
	Net/Gross weight	kg	17.5/20.5	17.5/20	17.5/20	17.5/20	22.5/26	22.5/26
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9
	Drain piping	mm	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25
Standard controller			Wired controller KJR-29B1/BK-E (6 meters connection wire)					

Indoor units lineup

Model			KMV-H713AMD	KMV-H803AMD	KMV-H903AMD	KMV-H1123AMD	KMV-H1403AMD
Power Supply			220 ~ 240V-1Ph-50Hz				
Capacity	Cooling	kW	7.1	8	9	11.2	14
		kcal/h	6,100	6,900	7,700	9,600	12,000
		btu/h	24,200	27,300	30,700	38,200	47,800
	Heating	kW	8	9	10	12.5	15.5
		kcal/h	6,900	7,700	8,600	10,800	13,300
		Btu/h	27,300	30,700	34,100	42,700	52,900
Power (Cooling)	Input	W	105	198	200	313	274
	Rated Current	A	0.47	1.0	1.0	1.8	1.55
Power (Heating)	Input	W	105	198	200	313	274
	Rated Current	A	0.47	1.0	1.0	1.8	1.55
Indoor air flow (SH/H/M/L)		m³/h	1127(30pa)/1029/934/781	1388(50pa)/1345/1165/1013	1388(50pa)/1345/1165/1013	1851(80pa)/1800/1556/1400	1745(100pa)/1905/1636/1400
		CFM	663/606/550/460	817/792/686/596	817/792/686/596	1,089/1,059/916/824	1,027/1121/963/824
ESP (external static pressure)		Pa	10(10~30)	20(10~50)	20(10~50)	40(10~80)	40(10~100)
Sound pressure level(H/M/L)		dB(A)	41.4/39/35	45.4/39.8/37	45.4/39.8/37	48.0 /41.9/38	47.7/43.2/39.0
Refrigerant	Type		R410A				
	Control method		EXV				
Net dimension	W×H×D	mm	1,180x210x500	1,230×270×775	1,230×270×775	1,230×270×775	1,290×300×865
Packing dimension	W×H×D	mm	1,335x285x525	1,355×350×795	1,355×350×795	1,355×350×795	1,400×375×925
Net/Gross Weight		kg	28/31.5	38/46.5	40/48	40/48	49/58
Piping Connections	L(flare)	mm	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ9.53
	G(Flare)	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	OD Φ25	OD Φ25	OD Φ25	OD Φ25	OD Φ25
Standard controller		-	Wired controller KJR-29B1/BK-E (6 meters connection wire)				

Notes:
1. Nominal cooling capacities are based on the following conditions: return air temperature: 27°CDB, 19°CWB, and outdoor temperature:35°CDB, equivalent ref. piping: 8m (horizontal)
2. Nominal heating capacities are based on the following conditions: return air temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, and equivalent ref. Piping: 8m (horizontal)
3. Sound level is measured at 1.4m below the air out-let.
* External static pressure is based on high speed indoor air flow.
* Specifications are subject to change without prior notice for product improvement.

60Hz Specifications

Model			KMV-H15 3AND	KMV-H22 3AND	KMV-H28 3AND	KMV-H36 3AND	KMV-H45 3AND	KMV-H56 3AND
Power supply			1-phase,208-230V,60Hz					
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1
		kcal/h	1900	2400	3100	3900	4800	6100
		Btu/h	7500	9600	12300	15400	19100	24200
Heating capacity		kW	2.6	3.2	4.0	5.0	6.3	8.0
		kcal/h	2200	2800	3400	4300	5400	6900
		Btu/h	8200	10900	13600	17100	21500	27300
Rated input	Cooling	W	66	72	77	100	100	125
	Heating		66	72	77	100	100	125
Rated current	Cooling	A	0.24	0.24	0.28	0.48	0.48	0.6
	Heating		0.24	0.24	0.28	0.48	0.48	0.6
Airflow rate(SH/H/M/L)		m³/h	588(30pa) /538/456/375	588(30pa) /538/456/375	614(30pa) /597/514/429	763(30pa) /811/684/575	763(30pa) /811/684/575	1127(30pa)/1029/934 /781
		CFM	346/317/268/221	346/317/268/221	361/351/303/253	449/477/403/338	449/477/403/338	663/606/550/460
ESP(external static pressure)		Pa	10(10-30)	10(10-30)	10(10-30)	10(10-30)	10(10-30)	10(10-30)
Sound pressure level(H/M/L)		dB(A)	36/35/32	36/35/32	38.6/37.5/33.8	39/37.9/34	39/37.9/34	41.4/39/35
Refrigerant		Type	R410A					
		Control method	EXV					
Indoor Unit	Net dim.(W×H×D)	in.(mm)	29-9/64x8-17/64x19-11/16(740x210x500)			37-51/64x8-17/64x19-11/16(960x210x500)	37-51/64x8-17/64x19-11/16(960x210x500)	46-29/64x8-17/64x19-11/16(1180x210x500)
	34-1/4×11-7/32×20-43/64(870×285×525)			43-57/64×11-7/32×20-43/64 (1115×285×525)	43-57/64×11-7/32×20-43/64 (1115×285×525)	52-9/16×11-7/32×20-43/64 (1335×285×525)		
	Net/Gross weight	lbs.(kg)	38.6/44.1(17.5/20)	38.6/44.1(17.5/20)	38.6/44.1(17.5/20)	49.6/57.3(22.5/26)	49.6/57.3(22.5/26)	61.8/69.5(28/31.5)
Piping connections	L(flare)	in.(mm)	1/4(Φ6.35)	1/4(Φ6.35)	1/4(Φ6.35)	1/4(Φ6.35)	3/8(Φ9.53)	3/8(Φ9.53)
	G(flare)	in.(mm)	1/2(Φ12.7)	1/2(Φ12.7)	1/2(Φ12.7)	1/2(Φ12.7)	5/8(Φ15.9)	5/8(Φ15.9)
	Drain piping	in.(mm)	OD 63/64(Φ25)	OD 63/64(Φ25)	OD 63/64(Φ25)	OD 63/64(Φ25)	OD 63/64(Φ25)	OD 63/64(Φ25)
Standard controller			Wired controller KJR-29B1/BK-E (6 meters connection wire)					

Model			KMV-H803AMD	KMV-H903AMD	KMV-H1123AMD	KMV-H1403AMD
Power supply			1-phase,208-230V,60Hz			
Cooling capacity		kW	8	9	11.2	14
		kcal/h	6900	7700	9600	12000
		Btu/h	27300	30700	38200	47800
Heating capacity		kW	9	10	12.5	15.5
		kcal/h	7700	8600	10800	13300
		Btu/h	30700	34100	42700	52900
Rated input	Cooling	W	133	134	378	352
	Heating		133	134	378	352
Rated current	Cooling	A	1	1	1.8	1.55
	Heating		1	1	1.8	1.55
Airflow rate (SH/H/M/L)		m³/h	1,388(50pa)/1,345/1,165/1,013	1,388(50pa)/1,345/1,165/1,013	1,851(80pa)/1,800/1,556/1,400	1,745(100pa)/1,905/1,636/1,400
		CFM	817/792/686/596	817/792/686/596	1,089/1,059/916/824	1,027/1,121/963/824
ESP(external static pressure)		Pa	20(10-50)	20(10-50)	40(10-80)	40(10-100)
Sound pressure level(H/M/L)		dB(A)	45.4/39.8/37	45.4/39.8/37	48.0/41.9/38	47.7/43.2/39
Refrigerant		Type	R410A			
		Control method	EXV			
Indoor Unit	Net dim.(W×H×D)	in.(mm)	48-27/64×10-5/8×30-33/64(1230×270×775)			50-25/32×11-13/16×34-1/16(1290×300×865)
	Gross dim.(W×H×D)		53-11/32×13-25/31×31-19/64 (1355×350×795)			55-1/8×14-49/64×36-27/64(1400×375×925)
	Net/Gross weight	lbs.(kg)	84/102.5(38/46.5)	88.2/105.8 (40/48)	88.2/105.8 (40/48)	108.0/127.9(49/58)
Piping connections	L(flare)	in.(mm)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)
	G(flare)	in.(mm)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)
	Drain piping	in.(mm)	OD 63/64(Φ25)			
Standard controller			Wired controller KJR-29B1/BK-E (6 meters connection wire)			

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temperature: 80.6°F(27°C)DB,66.2°F(19°C)WB,and outdoor temperature: 95°F(35°C)DB,equivalent ref. piping: 26.25ft. (8m) (horizontal)


2. Nominal heating capacities are based on the following conditions: return air temperature: 68°F(20°C)DB, outdoor temperature: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. piping: 26.25ft. (8m) (horizontal)

3. Sound Level is measured 4.59ft. (1.4m) below the unit.

* external static pressure are based on high speed indoor airflow.

* Specifications are subject to change without prior notice for product improvement.



High Static Pressure Duct



- Auto Restart
- Auto Addressing
- Follow Me
- Anti-Cold Air Function
- Connectable To Duct
- Wired Controller

Flexible duct design

External static pressure can be up to 196Pa (models 71 to 160) or 280Pa (models 200 to 560).



The maximum distance for air supply is about 14m at height of 6.5m.
With a 420mm (models 71 to 160) thick body, the minimum distance required above the ceiling is 450mm.

Greater flexibility with the four-speed fan

Four speed fan motor(model 71 to 160)

Convenient installation

The EXV is fixed inside the indoor unit (models 70-160), requires no extra connection.
Standard filter is housed in an aluminum frame, which is removable from the bottom in the downward direction.
Flange for air in/outlet duct connection is standard.

Flexible control and convenient for maintenance


Wired remote controller KJR-29B1/BK-E is as standard, and wireless remote controller RM05/BG(T)E-A is as an option.

The display board is connected to the E-box in factory, easier troubleshooting by LED display.

Easy access filters both at the rear & bottom


Standard functional port such as remote on/off dry contact.

Option



Drain pump with 750mm pump head is optional (models 71 to 160)

Double-skin drainage pan



Double-skin drainage pan provide double protection for ceilings (models 71 to 160 and models 400 to 560)

50Hz Specifications

Model			KHV-H713AMD	KHV-H803AMD	KHV-H903AMD	KHV-H1123AMD	KHV-H1403AMD	KHV-H1603AMD
Power Supply			220 ~ 240V-1Ph-50Hz					
Capacity	Cooling	kW	7.1	8	9	11.2	14	16
		kcal/h	6,100	6,900	7,700	9,600	12,000	13,800
		Btu/h	24,200	27,300	30,700	38,200	47,800	54,600
	Heating	kW	8	9	10	12.5	16	17
		kcal/h	6,900	7,700	8,600	10,800	13,800	14,600
		Btu/h	27,300	30,700	34,100	42,700	54,600	58,000
Power (Cooling)	Input	W	263	263	423	524	724	940
	Rated Current	A	1.23	1.23	1.87	2.3	2.85	4.77
Power (Heating)	Input	W	263	263	423	524	724	940
	Rated Current	A	1.23	1.23	1.87	2.3	2.85	4.77
Indoor air flow (H/M/L)		m³/h	1,443/1,361/1,218	1,416/1,338/1,220	1,951/1,741/1,518	2,116/1,936/1,520	3,000/2,618/2,226	3,620/3,044/2,744
		CFM	849/801/717	883/788/718	1,148/1,025/893	1,246/1,140/895	1,766/1,541/1,310	2,131/1,792/1,615
ESP (external static pressure)		Pa	25(25~ 196)	37(37~ 196)	37(37~ 196)	50(50~ 196)	50(50~ 196)	50(50~ 196)
Sound pressure level(H/M/L)		dB(A)	48/46/44	48/46/44.5	52/49/47	52/49/47	53/50/48	54/52/50
Refrigerant	Type	R410A						
	Control method	EXV						
Net dimension	W×H×D	mm	952×420×690	952×420×690	952×420×690	952×420×690	1,300×420×691	1,300×420×691
Packing dimension	W×H×D	mm	1,090×440×768	1,090×440×768	1,090×440×768	1,090×440×768	1,436×450×768	1,436×450×768
Net/Gross weight		kg	45/50	45/50	46.5/52.4	50.6/56	68/70	70/77.5
Piping connections	L(flare)	mm	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	ODΦ32	ODΦ32	ODΦ32	ODΦ32	ODΦ32	ODΦ32
Standard controller		-	Wired controller KJR-29B1/BK-E (6 meters connection wire)					

Model			KHV-H2003AMD	KHV-H2503AMD	KHV-H2803AMD	KHV-H4003AMD	KHV-H4503AMD	KHV-H5603AMD
Power Supply			220 ~ 240V-1Ph-50Hz					
Capacity	Cooling	kW	20	25	28	40	45	56
		kcal/h	17,200	21,500	24,100	34,400	38,700	48,200
		Btu/h	68,200	85,300	95,500	136,500	153,500	191,100
	Heating	kW	22.5	26	31.5	45	50	63
		kcal/h	19,400	22,400	27,100	38,700	43,000	54,200
		Btu/h	76,800	88,700	107,500	153,500	170,600	214,960
Power (Cooling)	Input	W	1516	1516	1516	2700	2700	3400
	Rated Current	A	8.6	8.6	8.6	12.5	12.5	15.5
Power (Heating)	Input	W	1516	1516	1516	2700	2700	3400
	Rated Current	A	8.6	8.6	8.6	12.5	12.5	15.5
Indoor air flow (H/M/L)		m³/h	4,700/4,100/3,599	4,700/4,100/3,599	4,700/4,100/3,599	7,472/6,072/4,995	7,472/6,072/4,995	9,550/7,950/6,600
		CFM	2,766/2,413/2,118	2,766/2,413/2,118	2,766/2,413/2,118	4,398/3,574/2,940	4,398/3,574/2,940	5,621/4,679/3,884
ESP (external static pressure)		Pa	200(50~280)	200(50~280)	200(50~280)	200(50~280)	200(50~280)	200(50~280)
Sound pressure level(H/M/L)		dB(A)	59/55/52	59/55/52	59/55/52	61/59/56	61/59/56	63/60/57
Refrigerant	Type	R410A						
	Control method	EXV						
Net dimension	W×H×D	mm	1,443×470×810	1,443×470×810	1,443×470×810	1,970×668×902.5	1,970×668×902.5	1,970×668×902.5
Packing dimension	W×H×D	mm	1,509×550×990	1,509×550×990	1,509×550×990	2,095×800×964	2,095×800×964	2,095×800×964
Net/Gross weight		kg	115/129	115/129	115/129	232/245	232/245	235/250
Piping connections	L(flare)	mm	Φ9.53×2	Φ9.53×2	Φ9.53×2	Φ12.7×2	Φ12.7×2	Φ15.9×2
	G(flare)	mm	Φ15.9×2	Φ15.9×2	Φ15.9×2	Φ22.2x2	Φ22.2x2	Φ28.6×2
	Drain piping	mm	ODΦ32	ODΦ32	ODΦ32	ODΦ32	ODΦ32	ODΦ32
Standard controller		-	Wired controller KJR-29B1/BK-E (6 meters connection wire)					

- Notes:
- 1. Nominal cooling capacities are based on the following conditions: return air temperature: 27°CDB, 19°CWB, and outdoor temperature:35°CDB, equivalent ref. piping: 8m (horizontal)
 - 2. Nominal heating capacities are based on the following conditions: return air temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, and equivalent ref. Piping: 8m (horizontal)
 - 3. Sound level is measured at 1.4m below the air out-let.
 - * External static pressure is based on high speed indoor air flow.
 - * Specifications are subject to change without prior notice for product improvement.

60Hz Specifications

Model			KHV-H713AND	KHV-H803AND	KHV-H903AND	KHV-H1123AND
Power Supply			208~230V-1Ph-60Hz			
Capacity	Cooling	kW	7.1	8	9	11.2
		kcal/h	6,100	6,900	7,700	9,600
		Btu/h	24,200	27,300	30,700	38,200
	Heating	kW	8	9	10	12.5
		kcal/h	6,900	7,700	8,600	10,800
		Btu/h	27,300	30,700	34,100	42,700
Power input	Cooling	W	414	402	409	409
	Heating		414	402	409	409
Rated current	Cooling	A	1.8	1.8	1.8	2.01
	Heating		1.8	1.8	1.8	2.01
Indoor air flow (H/M/L)		m³/h	1683/1550/1317	1683/1550/1317	2240/2020/1590	2186/1975/1560
		CFM	990/912/775	990/912/775	1318/1188/935	1286/1162/918
EXP (external static pressure)		Pa	40(30~196)	40(30~196)	40(30~196)	50(30~ 196)
Sound pressure level(H/M/L)		dB(A)	48/46/44.5	48/46/44.5	52/49/47	52/49/47
Refrigerant	Type		R410A			
	Control method		EXV			
Net dimension	W×H×D	in.(mm)	37-31/64×16-17/32×27-11/64(952×420×690)			
Packing dimension	W×H×D	in.(mm)	42-29/32×17-21/64×30-15/64(1090×440×768)			
Net/Gross weight		lbs.(kg)	102.6/114.7(46.5/52)	102.6/114.7(46.5/52)	110.3/124.6(50/56.5)	110.3/124.6(50/56.5)
		in.(mm)				
Piping connections	L(flare)	in.(mm)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)
	G(flare)	in.(mm)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)
	Drain piping	in.(mm)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)
Standard controller		-	Wired controller KJR-29B1/BK-E (6m wrie is standard)			

Model			KHV-H1403AND	KHV-H1603AND	KHV-H2003AND	KHV-H2503AND	KHV-H2803AND	KHV-H4003AND	KHV-H4503AND
Power Supply									
Capacity	Cooling	kW	14	16	20	25	28	40	45
		kcal/h	12,000	13,800	17,200	21,500	24,100	34400	38,700
		Btu/h	47,800	54,600	68,200	85,300	95,500	136500	153,500
	Heating	kW	16	16.5	22.5	26	31.5	45	50
		kcal/h	13,800	14,200	19,400	22,400	27,100	38700	43,000
		Btu/h	54,600	56,300	76,800	88,700	107,500	153,500	170600
Power input	Cooling	W	527	532	1516	1516	1516	1,600	1,600
	Heating	A	527	532	1516	1516	1516	1,600	1,600
Rated current	Cooling	W	2.03	2.31	8.6	8.6	8.6	7.5	7.5
	Heating	A	2.03	2.31	8.6	8.6	8.6	7.5	7.5
Indoor air flow (H/M/L)		m³/h	2,969/2,694/2,469	2,969/2,694/2,469	4,700/4,100/3,599	4,700/4,100/3,599	4,700/4,100/3,599	7,180/6,150/4,600	7,180/6,150/4,600
		CFM	1,746/1,586/1,453	1,746/1,586/1,453	2,766/2,413/2,118	2,766/2,413/2,118	2,766/2,413/2,118	4,226/3,620/2,708	4,226/3,620/2,708
ESP (external static pressure)		Pa	50(50~ 196)	50(50~ 196)	200(50~280)	200(50~280)	200(50~280)	200(50~280)	200(50~280)
Sound pressure level(H/M/L)		dB(A)	53/50/48	54/52/50	59/55/52	59/55/52	59/55/52	61/59/56	61/59/56
Refrigerant	Type		R410A						
	Control method		EXV						
Net dimension	W×H×D	mm	51-3/16×15-3/4×27-13/64(1300×420×691)			56-13/16×18-1/2×31-57/64(1443×470×810)		77-9/16×15-3/4×35-17/32(1970×668×902.5)	
Packing dimension	W×H×D	mm	56-17/32×17-23/32×30-15/64(1436×450×768)			59-13/32×21-21/32×38-31/32(1509×550×990)		82-31/64×31-1/2×37-61/64(2,095×800×964)	
Net/Gross Weight		kg	149.9/154.3(68/70)	153.3/167.6(69.5/76)	254/284(115/129)			518/551(235/250)	518/551(235/250)
Piping Connections	L(flare)	mm	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)×2			Φ3/8(Φ9.53)×2	Φ3/8(Φ9.53)×2
	G(flare)	mm	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)×2			Φ7/8(Φ22.2)×2	Φ7/8(Φ22.2)×2
	Drain piping	mm	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)	OD 1-17/64(Φ32)			OD 1-17/64(Φ32)	OD 1-17/64(Φ32)
Standard Controller		-	Wired controller KJR-29B1/BK-E (6 meters connection wire)						

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temperature: 80.6°F(27°C)DB,66.2°F(19°C)WB, outdoor temperature: 95°F(35°C)DB, equivalent ref. piping: 26.25ft.(8m)(horizontal).

2. Nominal heating capacities are based on the following conditions: return air temperature: 68°F(20°C)DB,outdoor temperature: 44.6°F(7°C)DB, 42.8°F(6°C)WB,equivalent ref. piping: 26.25ft.(8m)(horizontal).

3. Sound level is measured at 4.59ft.(1.4m) below the air outlet.

External static pressure is based on high speed indoor air flow.

4. KHV-H2003AND, KHV-H2503AND, KHV-H2803AND can be customized.

Indoor units lineup

Ceiling & Floor



Auto Restart



Cleanable Panel



Auto Addressing



Anti-Cold Air Function




Follow Me



LED Display

Convenient installation



The unit can be installed either horizontally on the ceiling or vertically against the wall.

- The slim and sleek structure design ensures easy installation.
- It can be installed into a corner of the ceiling even if the ceiling is very narrow.

Auto swing and wide angle air flow



- Two direction auto swing - vertical and horizontal.
- The range of horizontal air discharge is widened which secures wider air flow distribution to provide more comfortable air circulation no matter where the units is set up.
- Three air flow speeds: low, medium and high; double air guides.

More comfortable

- Adopt electrical expansion valve, ensuring precise flow control, lower modulation noise when EXV operating.
- Low noise operations; minimum 36 dB(A).
- Smoother airflow and less turbulence due to the multi-blade fan and the air guide design.

50Hz Specifications

Model			KXV-H363AMD	KXV-H453AMD	KXV-H563AMD	KXV-H713AMD	KXV-H803AMD
Power supply			1-phase, 220-240V, 50Hz				
Cooling capacity		kW	3.6	4.5	5.6	7.1	8
		kcal/h	3,100	3,900	4,800	6,100	6,900
		Btu/h	12,300	15,400	19,100	24,200	27,300
Heating capacity		kW	4	5	6.3	8	9
		kcal/h	3,400	4300	5,400	6,800	7,700
		Btu/h	13,600	17,100	21,500	27,300	30,700
Power input	Cooling	W	49	120	122	125	130
	Heating		49	120	122	125	130
Rated current	Cooling	A	0.23	0.67	0.67	0.67	0.83
	Heating		0.23	0.67	0.67	0.67	0.83
Airflow rate(H/M/L)		m³/h	650/570/500	800/600/500	800/600/500	800/600/500	1,200/900/700
		CFM	383/335/294	471/353/294	471/353/294	471/353/294	706/530/412
Sound pressure level(H/M/L)		dB(A)	40/38/36	43/41/38	43/41/38	43/41/38	45/43/40
Refrigerant		Type	R410A				
		Control method	EXV				
Net dimension(W×H×D)		mm	990×203×660	990×203×660	990×203×660	990×203×660	1,280×203×660
Packing dimension(W×H×D)		mm	1,089×296×744	1,089×296×744	1,089×296×744	1,089×296×744	1,379×296×744
Net weight		kg	26	28	28	28	34.5
Gross weight		kg	32	34	34	34	41
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	OD Φ16	OD Φ16	OD Φ16	OD Φ16	ODΦ16
Standard Controller		-	Wireless remote controller(RM05/BG(T)E-A)				

Model			KXV-H903AMD	KXV-H1123AMD	KXV-H1403AMD	KXV-H1603AMD
Power supply			1-phase, 220-240V, 50Hz			
Cooling capacity		kW	9	11.2	14	16
		kcal/h	7,700	9,600	13,300	13,800
		Btu/h	30,700	38,200	47,800	54,600
Heating capacity		kW	10	12.5	15	18
		kcal/h	8,600	10,800	12,900	15,500
		Btu/h	34,100	42,700	51,200	61,400
Power input	Cooling	W	130	182	182	300
	Heating		130	182	182	300
Rated current	Cooling	A	0.83	1.11	1.11	1.41
	Heating		0.83	1.11	1.11	1.41
Airflow rate(H/M/L)		m³/h	1,200/900/700	1,980/1,860/1,730	1,980/1,860/1,730	1,980/1,860/1,730
		CFM	706/530/412	1,165/1,095/1,018	1,165/1,095/1,018	1,165/1,095/1,018
Sound pressure level(H/M/L)		dB(A)	45/43/40	47/45/42	47/45/42	47/45/42
Refrigerant		Type	R410A			
		Control method	EXV			
Net dimension(W×H×D)		mm	1,280×203×660	1,670×244×680	1,670×244×680	1,670×285×680
Packing dimension(W×H×D)		mm	1,379×296×744	1,764×329×760	1,764×329×760	1,775×377×760
Net weight		kg	34.5	54	54	57.5
Gross weight		kg	41	59	59	63.5
Piping connections	L(flare)	mm	Φ9.53	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	ODΦ16	ODΦ16	ODΦ16	ODΦ16
Standard Controller		-	Wireless remote controller(RM05/BG(T)E-A)			

Notes:

1. Nominal cooling capacities are based on the following conditions: return airtemperature.: 27°CDB, 19°CWB, and outdoor temperature.:35°CDB, equivalent ref. piping: 8m (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temperature.: 20°CDB, outdoor temp.: 7°CDB, 6°CWB, and equivalent ref. Piping: 8m (horizontal)

3. Floor standing :Sound level is measured 1m from air-outlet in horizontal distance, 1m above the floor in vertical distance.

 Ceiling mounted:Sound level is measured 1m from air-outlet in horizontal distance, 1m from air-outlet in vertical distance.

* Specifications are subject to change without prior notice for product improvement.

Indoor units lineup


60Hz Specifications







Model			KXV-H363AND	KXV-H453AND	KXV-H563AND	KXV-H713AND
Power supply			220~240V-1Ph-60Hz			
Cooling capacity		kW	3.6	4.5	5.6	7.1
		kcal/h	3,100	3,900	4,800	6,100
		Btu/h	12,300	15,400	19,100	24,200
Heating capacity		kW	4	5	6.3	8
		kcal/h	3,400	4300	5,400	6,800
		Btu/h	13,600	17,100	21,500	27,300
Power input	Cooling	W	50	148	148	148
	Heating		50	148	148	148
Rated current	Cooling	A	0.55	0.55	0.55	0.57
	Heating		0.55	0.55	0.55	0.57
Airflow rate(H/M/L)		m³/h	600/480/400	750/650/550	750/650/550	750/650/550
		CFM	353/283/235	441/383/324	441/383/324	441/383/324
Sound pressure level(H/M/L)		dB(A)	40/38/36	43/41/38	43/41/38	43/41/38
Refrigerant		Type	R410A			
		Control method	EXV			
Net dimension(W×H×D)		in.(mm)	38-31/32×7-63/64×25-63/64(990×203×660)			
Packing dimension(W×H×D)		in.(mm)	42-7/8x11-21/32x29-9/32(1089x296x744)			
Net/Gross weight		lbs.(kg)	57.3/70.6(26/32)	61.7/75.0(28/34)	61.7/75.0(28/34)	61.7/75.0(28/34)
Piping connections	L(flare)	in.(mm)	1/4(Φ6.35)	1/4(Φ6.35)	3/8(Φ9.53)	3/8(Φ9.53)
	G(flare)	in.(mm)	1/2(Φ12.7)	1/2(Φ12.7)	5/8(Φ15.9)	5/8(Φ15.9)
	Drain piping	in.(mm)	OD 5/8(Φ16)	OD 5/8(Φ16)	OD 5/8(Φ16)	OD 5/8(Φ16)
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)			

Model			KXV-H803AND	KXV-H903AND	KXV-H1123AND	KXV-H1403AND	KXV-H1603AND
Power supply			220~240V-1Ph-60Hz				
Cooling capacity		kW	8	9	11.2	14	16
		kcal/h	6,900	7,700	9,600	12,000	13,800
		Btu/h	27,300	30,700	38,200	47,800	54,600
Heating capacity		kW	9	10	12.5	15	18
		kcal/h	7,700	8,600	10,800	12,900	15,477
		Btu/h	30,700	34,100	42,700	51,200	61,400
Power input	Cooling	W	183	183	245	245	378
	Heating		183	183	245	245	378
Rated current	Cooling	A	0.6	0.6	0.83	0.83	1.75
	Heating		0.6	0.6	0.83	0.83	1.75
Airflow rate(H/M/L)		m³/h	1,200/900/700	1,200/900/700	1,980/1,860/1,730	1,980/1,860/1,730	2,300/2,100/1,800
		CFM	706/530/412	706/530/412	1,165/1,095/1,018	1,165/1,095/1,018	1,354/1,236/1,060
Sound pressure level(H/M/L)		dB(A)	45/43/40	45/43/40	47/45/42	47/45/42	47/45/42
Refrigerant		Type	R410A				
		Control method	EXV				
Net dimension(W×H×D)		in.(mm)	50-25/64×7-63/64×25-63/64(1280×203×660)		65-3/4 x9-39/64x26-49/64(1670 x244x680)		65-3/4x11-7/32x26-49/64(1670x285x680)
Packing dimension(W×H×D)		in.(mm)	54-19/64x11-21/32x29-19/64(1379x296x744)		69-29/64 x12-61/64x29-59/64(1764x329x760)		69-7/8x14-27/32x29-59/64(1775x377x760)
Net/Gross weight		lbs.(kg)	76.1/90.4(34.5/41)	76.1/90.4(34.5/41)	119.0/130.1(54/59)	119.0/130.1(54/59)	126.5/139.7(57.5/63.5)
Piping connections	L(flare)	in.(mm)	3/8(Φ9.53)	3/8(Φ9.53)	3/8(Φ9.53)	3/8(Φ9.53)	3/8(Φ9.53)
	G(flare)	in.(mm)	5/8(Φ15.9)	5/8(Φ15.9)	5/8(Φ15.9)	5/8(Φ15.9)	5/8(Φ15.9)
	Drain piping	in.(mm)	OD 5/8(Φ16)	OD 5/8(Φ16)	OD 5/8(Φ16)	OD 5/8(Φ16)	OD 5/8(Φ16)
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)				

- Notes:
- Nominal cooling capacities are based on the following conditions: return air temperature: 80.6°F(27°C)DB,66.2°F(19°C)WB,and outdoor temperature: 95°F(35°C)DB,equivalent ref. piping: 26.25ft. (8m) (horizontal)
 - Nominal heating capacities are based on the following conditions: return air temperature: 68°F(20°C)DB, outdoor temperature: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft.(8m) (horizontal)
 - Floor standing :Sound level is measured 3.28ft(1m) from air-outlet in horizontal distance, 3.28ft(1m) above the floor in vertical distance.
Ceiling mounted:Sound level is measured 3.28ft(1m) from air-outlet in horizontal distance,3.28ft(1m) from air-outlet in vertical distance.

Wall-mounted




-  Auto Restart
-  Auto Addressing
-  Cleanable Panel
-  Anti-Cold Air Function
-  Follow Me
-  LED Display

Panel with LED display

The front panel and display panel have different colors to choose: white and brown for big panel, blue and brown for small panel.

Convenient installation


- Multi-refrigerant outlet pipe method: left\right\rear, more flexible for installation.
- For S panel,R panel & C panel , the EXV is built-in the indoor unit , compact size , longer the connection pipe;gas pipe:468mm;liquid pipe:550mm,more flexible for installation. For D panel, the EXV can be 5m far away from the indoor unit, which lower the noise.
- Adopts new type fixing plate, is easy to install and stable.



Indoor units lineup


Auto swing louver

The Auto Swing Louver function ensures that the air direction corresponds to the mode selected.



Easy maintenance

The front panel can be removed for easy maintenance access.



Optimal comfort through better flow control and quiet operations

The mechanical expansion valve offers 2,000-stage element positions to ensure precise flow control and less modulation noise when the EXV is operating for a quiet and comfortable environment. Three air flow speeds: low, medium and high; double air guides. Smoother airflow and less turbulence is ensured by the multi-blade fan and the air guide design.



S type panel (50hz)

Model			KWV-H153BMD	KWV-H223BMD	KWV-H283BMD	KWV-H363BMD	KWV-H453BMD	KWV-H563BMD
Power supply			1-phase,220-240V,50Hz					
Cooling capacity		kW	1.5	2.2	2.8	3.6	4.5	5.6
		kcal/h	1290	1900	2400	3100	3900	4800
		Btu/h	5100	7500	9600	12300	15400	19100
Heating capacity		kW	1.7	2.4	3.2	4	5	6.3
		kcal/h	1470	2100	2800	3400	4300	5400
		Btu/h	5800	8200	10900	13600	17100	21500
Rated input	Cooling	W	28	28	28	28	45	45
	Heating		28	28	28	28	45	45
Rated current	Cooling	A	0.12	0.14	0.14	0.14	0.2	0.2
	Heating		0.12	0.14	0.14	0.14	0.2	0.2
Airflow rate (H/M/L)		m³/h	427/389/336	525/480/430	525/480/430	590/520/480	860/755/630	925/860/755
		CFM	251/229/198	309/283/253	309/283/253	347/306/283	506/444/371	544/506/444
Sound pressure level(H/M/L)		dB(A)	33/31/28	35/32/29	35/32/29	35/32/29	40/38/34	40/38/34
Refrigerant		Type	R410A					
		Control method	EXV					
Indoor Unit	Net dim.(W×H×D)	mm	915×290×230	915×290×230	915×290×230	915×290×230	1072×315×230	1072×315×230
	Gross dim.(W×H×D)		1,020×390×315	1,020×390×315	1,020×390×315	1,020×390×315	1,180×415×315	1,180×415×315
	Net/Gross weight	kg	12.4/15.9	13/16.8	13/16.8	13/16.8	15.1/19.5	15.1/19.5
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9
	Drain piping	mm	ODΦ16.5	ODΦ16.5	ODΦ16.5	ODΦ16.5	ODΦ16.5	ODΦ16.5
Standard controller			Wireless remote controller (RM05/BG(T)E-A)					

C type panel (50hz)

Model			KWV-H223AMD	KWV-H283AMD	KWV-H363AMD	KWV-H453AMD	KWV-H563AMD
Power supply			1-phase, 220-240V, 50Hz				
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6
		kcal/h	1,900	2,400	3,100	3,900	4,800
		Btu/h	7,500	9,600	12,300	15,400	19,100
Heating capacity		kW	2.4	3.2	4	5	6.3
		kcal/h	2,100	2,800	3,400	4,300	5,400
		Btu/h	8,200	10,900	13,600	17,000	21,500
Power input	Cooling	W	28	28	28	45	45
	Heating		28	28	28	45	45
Rated current	Cooling	A	0.14	0.14	0.14	0.2	0.2
	Heating		0.14	0.14	0.14	0.2	0.2
Airflow rate(H/M/L)		m³/h	520/480/430	520/480/430	520/480/430	860/755/630	925/860/755
		CFM	306/283/253	306/283/253	306/283/253	506/444/371	544/506/444
Sound pressure level(H/M/L)		dB(A)	35/32/29	35/32/29	35/32/29	40/38/34	40/38/34
Refrigerant		Type	R410A				
		Control method	EXV				
Net dimension(W×H×D)		mm	915×290×210	915×290×210	915×290×210	1,070×315×210	1,070×315×210
Packing dimension(W×H×D)		mm	1,020×385×300	1,020×385×300	1,020×385×300	1,165×395×285	1,165×395×285
Net weight		kg	12	12	12	15	15
Gross weight		kg	17.5	17.5	17.5	19	18
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9
	Drain piping	mm	ODΦ16.5	ODΦ16.5	ODΦ16.5	ODΦ16.5	ODΦ16.5
Standard controller		-	Wireless remote controller(RM05/BG(T)E-A)				

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temperature: 27°CDB, 19°CWB, and outdoor temperature:35°CDB, equivalent ref. piping: 8m (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, and equivalent ref. Piping: 8m (horizontal)

3. Sound level is measured 1m below the air outlet horizontally and vertically.

★ Specifications are subject to change without prior notice for product improvement.

R type panel (50Hz)

Model			KWV-H713CMD	KWV-H803CMD	KWV-H903CMD
Power supply			1-phase, 220-240V, 50Hz		
Cooling capacity		kW	7.1	8	9
		kcal/h	6,100	6,900	7,700
		Btu/h	24,200	27,300	30,700
Heating capacity		kW	8	9	10
		kcal/h	6,900	7,700	8,600
		Btu/h	27,300	30,700	34,100
Power input	Cooling	W	75	86	86
	Heating		75	86	86
Rated current	Cooling	A	0.33	0.39	0.39
	Heating		0.33	0.39	0.39
Airflow rate(H/M/L)		m³/h	1,190/780/580	1,320/840/640	1,320/840/640
		CFM	700/459/341	776/494/376	776/494/376
Sound pressure level(H/M/L)		dB(A)	47/43/42	48/43/38	49/43/38
Refrigerant		Type	R410A		
		Control method	EXV		
Net dimension(W×H×D)		mm	1,250×325×245		
Packing dimension(W×H×D)		mm	1,345×430×335		
Net weight		kg	19.9		
Gross weight		kg	25		
Piping connections	L(flare)	mm	Φ9.53		
	G(flare)	mm	Φ15.9		
	Drain piping	mm	OD Φ16.5		
Standard controller		-	Wireless remote controller(RM05/BG(T)E-A)		

S type panel (60Hz)

Model			KWV-H223BND	KWV-H283BND	KWV-H363BND	KWV-H453BND	KWV-H563BND
Power supply			220~240V-1Ph-60Hz				
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6
		kcal/h	1,900	2,400	3,100	3,900	4,800
		Btu/h	7,500	9,600	12,300	15,400	19,100
Heating capacity		kW	2.4	3.2	4	5	6.3
		kcal/h	2,100	2,800	3,400	4,300	5,400
		Btu/h	8,200	10,900	13,600	17,100	21,500
Power input	Cooling	W	28	28	28	51	51
	Heating		28	28	28	51	51
Rated current	Cooling	A	0.14	0.14	0.14	0.2	0.2
	Heating		0.14	0.14	0.14	0.2	0.2
Airflow rate(H/M/L)		m³/h	525/480/430	525/480/430	590/520/480	860/755/630	925/860/755
		CFM	309/283/253	309/283/253	347/306/283	506/444/371	544/506/444
Sound pressure level(H/M/L)		dB(A)	35/32/29	35/32/29	35/32/29	40/38/34	40/38/34
Refrigerant		Type	R410A				
		Control method	EXV				
Net dimension(W×H×D)		in.(mm)	36-1/32x11-13/32x9-1/16(915×290×230)			42-7/32x12-13/32x9-1/16(1072×315×230)	
Packing dimension(W×H×D)		in.(mm)	40-5/32x15-11/32x12-13/32(1020×390×315)			46-15/32×16-11/32×12-13/32(1180×415×315)	
Net weight		lbs.(kg)	28.7(13)	28.7(13)	28.7(13)	33.4(15.1)	33.4(15.1)
Gross weight		lbs.(kg)	37.1(16.8)	37.1(16.8)	37.1(16.8)	43/19.5	43/19.5
Piping connections	L(flare)	in.(mm)	Φ1/4(Φ6.35)	Φ1/4(Φ6.35)	Φ1/4(Φ6.35)	Φ1/4(Φ6.35)	Φ3/8(Φ9.53)
	G(flare)	in.(mm)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)	Φ5/8(Φ15.9)
	Drain piping	in.(mm)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)				

Notes:
1. Nominal cooling capacities are based on the following conditions: return air temp. : 80.6°F(27°C)DB,66.2°F(19°C)WB,and outdoor temp.: 95°F(35°C)DB,equivalent ref. piping: 26.25ft(8m)(horizontal)
2. Nominal heating capacities are based on the following conditions: return air temp.: 68°F(20°C)DB, outdoor temp.: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft(8m)(horizontal)
3. Sound level is measured 3.28ft.(1m) below the air out-let both in horizontal and vertical distance.
* Specifications are subject to change without prior notice for product improvement.

C type panel (60Hz)

Model			KWV-H223AND	KWV-H283AND	KWV-H363AND	KWV-H453AND	KWV-H563AND
Power supply			220-240V~, 1Ph, 60Hz				
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6
		kcal/h	1,900	2,400	3,100	3,900	4,800
		Btu/h	7,500	9,600	12,300	15,400	19,100
Heating capacity		kW	2.4	3.2	4	5	6.3
		kcal/h	2,200	2,800	3,400	4,300	5,400
		Btu/h	8,900	10,900	13,600	17,100	21,500
Power input	Cooling	W	28	28	28	45	45
	Heating		28	28	28	45	45
Rated current	Cooling	A	0.14	0.14	0.14	0.2	0.2
	Heating		0.14	0.14	0.14	0.2	0.2
Airflow rate(H/M/L)		m³/h	557/520/467	557/520/467	557/520/467	842/722/597	842/722/597
		CFM	328/306/275	328/306/275	328/306/275	496/425/351	496/425/351
Sound pressure level(H/M/L)		dB(A)	35/32/29	35/32/29	35/32/29	40/38/34	40/38/34
Refrigerant		Type	R410A				
		Control method	EXV				
Net dimension(W×H×D)		in.(mm)	36-1/32x11-13/32x8-9/32(915×290×210)			42-7/32×12-13/32×8-9/32(1070×315×210)	
Packing dimension(W×H×D)		in.(mm)	40-5/32×15-5/32×11-13/16(1020×385×300)			45-7/8x15-9/16x11-7/32(1165×395x285)	
Net weight		lbs.(kg)	26.5(12)	26.5(12)	26.5(12)	33.1(15)	33.1(15)
Gross weight		lbs.(kg)	38.6(17.5)	38.6(17.5)	38.6(17.5)	41.9(19)	39.7(18)
Piping connections	L(flare)	in.(mm)	Φ1/4(Φ6.35)	Φ1/4(Φ6.35)	Φ1/4(Φ6.35)	Φ1/4(Φ6.35)	Φ3/8(Φ9.53)
	G(flare)	in.(mm)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)	Φ1/2(Φ12.7)	Φ5/8(Φ15.9)
	Drain piping	in.(mm)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)	OD 21/32(Φ16.5)
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)				

R type panel (60Hz)

Model			KWV-H713CND	KWV-H803CND	KWV-H903CND
Power supply			1-phase, 220-240V, 60Hz		
Cooling capacity		kW	7.1	8	9
		kcal/h	6,100	6,900	7,700
		Btu/h	24,200	27,300	30,700
Heating capacity		kW	8	9	10
		kcal/h	6,900	7,700	8,600
		Btu/h	27,300	30,700	34,100
Power input	Cooling	W	79	95	95
	Heating		79	95	95
Rated current	Cooling	A	0.33	0.39	0.39
	Heating		0.33	0.39	0.39
Airflow rate(H/M/L)		m³/h	1,190/780/580	1,320/840/640	1,320/840/640
		CFM	700/459/341	776/494/376	776/494/376
Sound pressure level(H/M/L)		dB(A)	45/42/39	48/43/38	49/43/38
Refrigerant		Type	R410A		
		Control method	EXV		
Net dimension(W×H×D)		in.(mm)	49-7/32×12-51/64×9-41/64(1250×325×245)		
Packing dimension(W×H×D)		in.(mm)	52-61/64×16-59/64×13-3/16(1345×430×335)		
Net weight		lbs.(kg)	43.8 （19.9）		
Gross weight		lbs.(kg)	55.1 （25）		
Piping connections	L(flare)	in.(mm)	Φ3/8(Φ9.53)		
	G(flare)	in.(mm)	Φ5/8(Φ15.9)		
	Drain piping	in.(mm)	OD 21/32(Φ16.5)		
Standard controller		-	Wireless remote controller (RM05/BG(T)E-A)		

Notes:


1. Nominal cooling capacities are based on the following conditions: return air temp. : 80.6°F(27°C)DB,66.2°F(19°C)WB,and outdoor temp.: 95°F(35°C)DB,equivalent ref. piping: 26.25ft(8m)(horizontal)

2. Nominal heating capacities are based on the following conditions: return air temp.: 68°F(20°C)DB, outdoor temp.: 44.6°F(7°C)DB,42.8°F(6°C)WB, and equivalent ref. Piping: 26.25ft(8m)(horizontal)

3. Sound level is measured 3.28ft.(1m) below the air out-let both in horizontal and vertical distance.

* Specifications are subject to change without prior notice for product improvement.

Floor Standing



-  Auto Restart
-  Cleanable Panel
-  Auto Addressing
-  Anti-Cold Air Function
-  Follow Me
-  LED Display

Easy installation

Floor standing types can be hung on the wall or installed on the floor. The floor type of unit can make cleaning and maintenance much easier. Running the piping from the rear allows the unit to be hung on walls. Cleaning under the unit, where dust tends to accumulate, is considerably easier.

Easy maintenance

Filter is provided as a standard accessory. It can be removed and cleaned easily thanks to Koolman's sophisticated design and the product's removable blades.

The streamlined appearance harmonizes the unit with a given room's interior decor. All metal parts are made of commercial grade galvanized steel for maximum protection against corrosion.

Optional panel styles

Concealed floor standing type



F3B series concealed type

Concealed type's body is concealed in the skirting board to improve aesthetics. The body is just 212mm deep, and can be installed at the room's perimeter. Special installation methods eliminate noise in the room area. Both air intake from front and air intake from below is optional for exposed floor standing type.



Air intake from front(F4 series)



Air intake from below(F5 series)

Indoor units lineup

Model			KDV-H223AMD	KDV-H283AMD	KDV-H363AMD	KDV-H453AMD	KDV-H563AMD	KDV-H713AMD	KDV-H803AMD
Power supply			1-phase,220-240V,50Hz						
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8
		kcal/h	1900	2400	3100	3900	4800	6100	6900
		Btu/h	7500	9600	12300	15400	19100	24200	27300
Heating capacity		kW	2.4	3.2	4	5	6.3	8	9
		kcal/h	2100	2800	3400	4300	5400	6900	7700
		Btu/h	8200	10900	13600	17100	21500	27300	30700
Rated input	Cooling	W	40	46	46	49	88	130	130
	Heating		40	46	46	49	88	130	130
Rated current	Cooling	A	0.18	0.21	0.22	0.22	0.4	0.56	0.59
	Heating		0.18	0.21	0.22	0.22	0.4	0.56	0.59
Airflow rate(H/M/L)		m³/h	530/456/400	569/485/421	624/522/375	660/542/440	1150/970/830	1380/1100/870	1380/1100/870
		CFM	312/268/235	335/285/248	367/307/221	388/319/259	677/571/489	812/647/512	812/647/512
Sound pressure level (H/M/L)		dB(A)	36/33/29	36/33/29	37/34/30	37/34/30	41/35/31	44/39/33	44/39/33
Refrigerant		Type	R410A						
		Control method	EXV						
Indoor Unit	Net dim.(W×H×D)	mm	840×545×212	840×545×212	1040×545×212	1040×545×212	1440×545×212	1440×545×212	1440×545×212
	Gross dim.(W×H×D)		939×639×305	939×639×305	1139×639×305	1139×639×305	1425×639×305	1425×639×305	1425×639×305
	Net/Gross weight	kg	25/27	25/27	29.5/34	29.5/34	33/39	33/39	36/40
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	ODΦ16	ODΦ16	ODΦ16	ODΦ16	ODΦ16	ODΦ16	ODΦ16
Standard controller			Wireless remote controller (RM05/BG(T)E-A)						

Model			KDV-H223BMD	KDV-H283BMD	KDV-H363BMD	KDV-H453BMD	KDV-H563BMD	KDV-H713BMD	KDV-H803BMD
			KDV-H223CMD	KDV-H283CMD	KDV-H363CMD	KDV-H453CMD	KDV-H563CMD	KDV-H713CMD	KDV-H803CMD
Power supply			1-phase, 220-240V, 50Hz						
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8
		kcal/h	1,900	2,400	3,100	3,900	4,800	6,100	6,900
		Btu/h	7,500	9,500	12,300	15,400	19,100	242,00	27,300
Heating capacity		kW	2.4	3.2	4	5	6.3	8	9
		kcal/h	2,100	2,800	3,400	4,300	5,400	6,900	7,700
		Btu/h	8,200	10,900	13,600	17,100	21,500	27,300	30,700
Power input	Cooling	W	40	46	46	49	88	130	130
	Heating		40	46	46	49	88	130	130
Rated current	Cooling	A	0.18	0.19	0.22	0.22	0.43	0.63	0.63
	Heating		0.18	0.19	0.22	0.22	0.43	0.63	0.63
Airflow rate(H/M/L)		m³/h	530/456/400	569/485/421	624/522/375	660/542/440	1,150/970/830	1,380/1,100/870	1,380/1,100/870
		CFM	312/268/235	335/285/248	367/307/221	388/319/259	677/571/489	812/647/512	812/647/512
Sound pressure level(H/M/L)	F4	dB (A)	36/33/29	36/33/29	37/34/30	37/34/30	41/35/31	44/39/33	44/39/33
	F5		36/33/29	36/33/29	37/34/30	37/34/30	41/35/31	44/39/33	44/39/33
Refrigerant	Type		R410A						
	Control method		EXV						
Net dimension (W×H×D)	F4	mm	1,000×596×225	1,000×596×225	1,200×596×225	1,200×596×225	1,500×596×225	1,500×596×225	1,500×596×225
	F5		1,000×677×220	1,000×677×220	1,200×677×220	1,200×677×220	1,500×677×220	1,500×677×220	1,500×677×220
Packing dimension (W×H×D)	F4	mm	1,089×683×312	1,089×683×312	1,289×683×312	1,289×683×312	1,589×683×312	1,589×683×312	1,589×683×312
	F5		1,182×683×312	1,182×683×312	1,382×683×312	1,382×683×312	1,682×683×312	1,682×683×312	1,682×683×312
Net/Gross weight	F4	kg	30/35	30/35	36/44	36/44	41/46.5	41/46.5	42.5/48.5
	F5		30/38	30/38	35.5/41	35.5/41	42/51	42/51	44/53
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	ODΦ16	ODΦ16	ODΦ16	ODΦ16	ODΦ16	ODΦ16	ODΦ16
Standard controller			Wireless remote controller(RM05/BG(T)E-A)						

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temperature: 27°CDB, 19°CWB, and outdoor temperature:35°CDB, equivalent ref. piping: 8m (horizontal)

2. Nominal heating capacities are based on the following conditions: return air temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, and equivalent ref. Piping: 8m (horizontal)

3. Sound level is measured 1m from the air out-let in horizontal distance and 1m above the floor in vertical distance.

* Specifications are subject to change without prior notice for product improvement.

Console



-  Auto Restart
-  Cleanable Panel
-  Auto Addressing
-  Anti-Cold Air Function
-  Follow Me
-  LED Display

Compact size and stylish

- The elegant and thin unit body complements the existing decor and saves space.
- The EXV is installed inside of the indoor unit for added compactness.

Flexible installation

- Can be installed on the floor or lower wall
- As a floor standing type, it can be semi or fully accessed without losing capacity.



Indoor units lineup

High Comfort

- Flexible air blow: vertical auto swing and wide angle louvers ensure that warm air reaches every corner of the room and increases the air flow coverage.
- Indoor unit adopts DC motor with five fan speeds to meet different requirements.
- Applies the Fujikoki mechanical expansion valve which offers 2,000-stage element positions to ensure precise flow control and lower modulation noise when the EXV is operating.

Powerful mode can be selected for rapid cooling or heating

COOLING MODE



Quick cooling

To maintain temperature

HEATING MODE




Anti-cold air

Normal operation

Two air outlets and four air inlets

Four directions of air inlet; two options of air outlet: Up and Down; or Up only.



Bottom, top, and right/left side, for better ventilation.

Low-noise design

Five-speed indoor unit; low noise; low power consumption.



Low noise operation, lowest to 26dB(A)


50Hz Specifications

Model			KCV-H223AMD	KCV-H283AMD	KCV-H363AMD	KCV-H453AMD
Power supply			1-phase, 220-240V, 50Hz			
Cooling capacity		kW	2.2	2.8	3.6	4.5
		kcal/h	1,900	2,400	3,100	3,900
		Btu/h	7,500	9,600	12,300	15,400
Heating capacity		kW	2.6	3.2	4.0	5.0
		kcal/h	2,200	2,800	3,400	4,300
		Btu/h	8,900	10,900	13,600	17,100
Power input	Cooling	W	20	25	25	45
	Heating		20	25	25	45
Rated current	Cooling	A	0.09	0.11	0.15	0.2
	Heating		0.09	0.11	0.15	0.2
Airflow rate(H/M/L)		m³/h	430/345/229	510/430/229	510/430/229	660/512/400
		CFM	253/203/135	300/253/135	300/253/135	388/300/235
Sound pressure level(H/M/L)		dB(A)	38/32/26	39/33/27	39/33/27	42/39/36
Refrigerant		Type	R410A			
		Control method	EXV			
Net dimension(W×H×D)		mm	700×210×600	700×210×600	700×210×600	700×210×600
Packing dimension(W×H×D)		mm	810×305×710	810×305×710	810×305×710	810×305×710
Net weight		kg	14	15	15	15
Gross weight		kg	19	20	20	20
Piping connections	L(flare)	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35
	G(flare)	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7
	Drain piping	-	OD Φ16	OD Φ16	OD Φ16	OD Φ16
Standard controller		Wireless remote controller(RM05/BG(T)E-A)				

Notes:

1. Nominal cooling capacities are based on the following conditions: return air temperature.: 27°CDB,19°CWB,outdoor temperature.:35°CDB, equivalent ref. Piping: 8m(horizontal)
2. Nominal heating capacities are based on the following conditions: return air temperature.: 20°CDB,outdoor temperature.: 7°CDB, 6°CWB,equivalent ref. Piping: 8m(horizontal)
3. Sound level is measured 1m from the air outlet in horizontal distance and 1m above the floor in vertical distance.


Fresh Air Processing Unit



Healthy and comfortable

Fresh air is imported, provides a healthy and comfortable living environment.

100% Fresh air processing unit



Both fresh air filtration and heating/cooling can be achieved in a single system.


Indoor units and fresh air processing unit can be connected to the same refrigerant system, increasing design flexibility and greatly reducing total system costs.

Indoor units lineup

High external static pressure

External static pressure can be up to 220Pa(models 125 to 140) and 260Pa(models 200 to 280) for more flexible duct applications. The maximum distance of air supply is about 14m and the maximum height of air supply is about 6.5m.

Innovative air supply technology for excellent room temperature control



50Hz Specifications

Model			KHAV-H1253AMD	KHAV-H1403AMD	KHAV-H2003AMD	KHAV-H2503AMD	KHAV-H2803AMD
Power Supply			1-phase, 220-240V, 50Hz				
Capacity	Cooling	kW	12.5	14	20	25	28
		kcal/h	10,800	12,000	17,200	21,500	24,100
		Btu/h	42,700	47,800	68,200	85,300	95,500
	Heating	kW	10.5	12	18	20	22
		kcal/h	9,000	10,300	15,550	17,200	18,900
		Btu/h	35,800	41,000	61,400	68,200	75,100
Power (Cooling)	Input	W	430	430	1063	1,063	1063
	Rated Current	A	2.4	2.4	5.3	5.6	5.6
Power (Heating)	Input	W	461	430	1063	1,063	1,063
	Rated Current	A	2.4	2.4	5.3	5.6	5.6
Air flow (H/M/L)		m³/h	2,142/1,870/1,611	2,142/1,870/1,611	2,870/2,620/2,150	3,005/2,700/2,250	3,005/2,700/2,250
		CFM	1,261/1101/948	1,261/1101/948	1,689/1,542/1,265	1,766/1,589/1,324	1,766/1,589/1,324
ESP (external static pressure)		Pa	50(50~196)	50(50~196)	200(50~280)	200(50~280)	200(50~280)
Sound pressure level(H/M/L)		dB(A)	54/52/50	54/52/50	54/53/51	55/54/52	55/54/52
Refrigerant	Type		R410A				
	Control method		EXV				
Net dimension	W×H×D	mm	1,300×420×690	1,300×420×690	1,443×470×810	1,443×470×810	1,443×470×810
Packing dimension	W×H×D	mm	1,436×450×768	1,436×450×768	1,509×550×990	1,509×550×990	1,509×550×990
Net/Gross weight		kg	69.5/76	69.5/76	115/125	115/125	115/125
Piping connections	L(flare)	mm	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ9.53
	G(flare)	mm	Φ15.9	Φ15.9	Φ15.9	Φ15.9	Φ15.9
	Drain piping	mm	OD Φ25	OD Φ25	OD Φ32	OD Φ32	OD Φ32
Standard controller		-	Wired controller KJR-29B1/BK-E (6 meters connection wire)				

60Hz Specifications


Model			KHAV-H1253AND	KHAV-H1403AND	KHAV-H2003AND	KHAV-H2503AND	KHAV-H2803AND
Power Supply			208 ~ 230V-1Ph-60Hz				
Capacity	Cooling	kW	12.5	14	20	25	28
		kcal/h	10,800	12000	17,200	21,500	24,100
		Btu/h	42,600	47,800	68,200	85,300	95,500
	Heating	kW	10.5	12	18	20	22
		kcal/h	9,000	10,300	15,500	17,200	18,900
		Btu/h	36,000	41,000	61,400	68,200	75,000
Power input	Cooling	W	468	468	616	616	616
	Heating		468	468	616	616	616
Rated current	Cooling	A	2.4	2.4	4.2	4.4	4.4
	Heating		2.4	2.4	4.2	4.4	4.4
Indoor air flow (H/M/L)		m³/h	2,142/1,870/1,611	2,142/1,870/1,611	2,870/2,620/2,150	3,005/2,700/2,250	3,005/2,700/2,250
		CFM	1,261/1,101/948	1,261/1,101/948	1,689/1,542/1,265	1,766/1,589/1,324	1,766/1,589/1,324
ESP (external static pressure)		Pa	50(50~196)	50(50~196)	200(50~280)	200(50~280)	200(50~280)
Sound pressure level(H/M/L)		dB(A)	54/52/50	53/50/48	54/53/51	55/54/52	55/54/52
Refrigerant	Type		R410A				
	Control method		EXV				
Net dimension	W×H×D	in.(mm)	51-3/16×16-17/32×27-11/64(1300×420×690)		56-13/16×18-1/2×31-57/64(1443×470×810)		
Packing dimension	W×H×D	in.(mm)	56-17/32×17-23/32×30-1/4(1,436×450×768)		59-13/32×21-21/32×38-31/32(1,509×550×990)		
Net/Gross weight		lbs.(kg)	153.2/167.5(69.5/76)	153.2/167.5(69.5/76)	251/274(114/124)	251/274(114/124)	251/274(114/124)
Piping connections	L(flare)	in.(mm)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)	Φ3/8(Φ9.53)
	G(flare)	in.(mm)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)	Φ5/8(Φ15.9)
	Drain piping	in.(mm)	OD 1-17/64(Φ32)				
Standard controller		-	Wired controller KJR-29B1/BK-E (6 meters connection wire)				

Notes:
1. Nominal cooling capacities are based on the following conditions: outdoor air temp.:91.4°F(33°C)DB, 75.2°F(24°C)WB, equivalent ref. piping:26.25ft. (8m)(horizontal).
2. Nominal heating capacities are based on the following conditions: outdoor air temp.:32°F(0°C)DB, 30.2°F(-1°C)WB, equivalent ref. piping:26.25ft. (8m)(horizontal).
3. Sound level is measured 4.59ft.(1.4m) from the air out-let.
* External static pressure are based on high speed indoor air flow.
* Specifications are subject to change without prior notice for product improvement.
* When outdoor-air processing units are connected, the total connection capacity must be within 50% to 100% of that of the outdoor units.
* When outdoor-air processing units and standard indoor units are connected, the total connection capacity of the outdoor-air processing units must not exceed 30% of that of the outdoor units.
* Outdoor-air processing units can be used without indoor units.
* The fresh air processing unit is not available for V4+R system.Connection Conditions:The following restrictions must be observed in order to maintain the indoor units connected to the same system.

Control Systems

Control Systems

Network Control



Individual control

Wired controller

KJR-10B KJR-86C
KJR-12B KJR-120B
KJR-90A KJR-90C
KJR-29B KJR-120C



Remote controller

RM02
RM05
R05
R06
R51
R71



Accessories

Card-key Interface MD-NIM05



MD-NIM05



Card-key



Wired controller

Infrared Sensor MD-NIM09



Infrared control box



Infrared sensor module



Wired controller

Outdoor units

Comparison of Controllers

Item		Remote controller			Wired Controller				Centralized Controller		
Model name		RM05/ RM02	R51/ R71	R05/ R06	KJR-10B /KJR-12B	KJR-120B	KJR-90A /KJR-86C	KJR-29B KJR-90C	CCM30/MD- CCM03	MD-CCM09	KJR- 90B
MAX. controllable IDU		/			1	1	1	1	64	64	16
A/C control function	On/Off	●	●	●	●	●	●	●	●	●	●
	Operation mode setting	●	●	●	●	●	●	●	●	●	●
	Fan speed setting	●	●	●	●	●	●	●	●	●	-
	Room temp. setting	●	●	●	●	●	●	●	●	●	-
	Vertical swing	●	●/-	●/-	-	-	-	-	-	-	-
	Horizontal swing	●	●	●	●	●	●/-	●	●	●	-
	Air direction	●/-	-/●	●	-	-	-	-	-	-	-
	Economic mode	●	●	●/-	●	●	-	-	-	-	-
	Central setting	-	-	-	-	-	-	-	●	●	●
	Keyboard lock	●	●/-	●	●	●	-	●	●	●	-
	Mode lock	-	-	-	-	-	-	-	●	●	-
	Remote signal receiving	-	-	-	-	-	-	●	-	-	-
	26°C shortcut setting	-/●	-	-	-	-	-/●	-	-	-	-
	Silent mode	-	-	-	-	●	-	●	-	-	-
Display	Backlight	●	●/-	●	-/●	●	-/●	●	●	●	●
	Current time	●/-	-	●	●/-	●	●/-	-	-	●	-
	RC prohibition	-	-	-	-	-	-	-	●	●	-
	Address	-	-	-	-	-	-	-	●	●	-
	Error code	-	-	-	-	●	-	-	●	●	-
	Room temp.	-	-	-	-	-	-/●	-	●	●	-
Timer	Period	-	-	-	-	-	-	-	-	Week	-
	On/Off per day	-	-	-	-	-	-	-	-	4	-
	On/Off per week	-	-	-	-	-	-	-	-	28	-
	On/Off timer	●	●	●	●	●	●/-	●	●	●	-
Control	FOLLOW ME	-/●	-	-	-/●	-	-	●	-	-	-
	Emergent stop	-	-	-	-	-	-	-	●	-	-
	Emergent start	-	-	-	-	-	-	-	●	-	-
	Address setting	●	-	-	●/-	-	-	●	-	-	-
	BMS access	-	-	-	-	-	-	-	●	-	-
	Control via internet	-	-	-	-	-	-	-	●	-	-
	Air filter cleaning reminding	-	-	-	●/-	●	-	●	●/-	-	-

● : Available controller functions
 — : Not available controller functions

Wireless Remote Controller



RM02



RM05



R05



R06



R51



R71

Functions


Portable device

The wireless remote controller is a portable control device that enables users to control the A/C anywhere within a distance of 11m.



Simplified user interface

Users can synchronize the air conditioners' parameters with the display panel on the wireless remote controller to precisely control a room's environment.



Background light


The background light allows users to operate the device in a dark room. The device lights up when a button is pressed, and turns off when a given operation is completed.



*The follow me function is available for RM02

Built-in timer

The built-in daily timer offers the convenience of automatically starting and stopping the system at set times.



The indoor unit is set to work in automode from 8:00 to 20:00

Setting addresses

Besides the machine's auto addressing function, users can set the indoor unit's address on the wireless remote controller RM05/RM02.



Specifications

Model	RM02	RM05	R05	R06	R51	R71
Dimensions (H×W×D)(mm)	150×60×15	150×65×20	150×65×20	100×55×20	140×60×15	125×42×27
Power (V)	1.5V(LR03/AAA)×2					


Wired Controller



KJR-29B




KJR-90C



Functions

Air filter cleaning reminding


The wired controller records the total running time of the indoor unit. When the accumulated running time reaches the pre-set value, it will remind users need to clean the air filter of the indoor unit. Clean the filter regularly can keep indoor air fresh and clean, good for your health.



*Available for KJR-10B/KJR-29B/KJR-90C model.

Silent mode

Under the cooling, heating and auto mode,when operate the silent mode, it can reduce the running noise through setting the fan speed to low. This will help you bring a quieter environment.



KJR-29B
(Touch key)

Remote signal receiving function

KJR-29B and KJR-90C provide a signal receiver for remote controller. Signal from remote controller can be received by a wired controller, then sent to the indoor unit and it conveniences to control.

Locking wired controller

The locking function can be used to prevent other people from using the controller.

Specifications

Model	29B	90C
Dimensions (H×W×D)(mm)	120×120×20	86×86×16.5
Power (V)	DC 5V	


Wired Controller



KJR-10B




KJR-12B



Functions

Follow me



With the FOLLOW ME function, the wired controller can detect the air temperature at the user' s altitude instead that of the ceiling or floor. This helps making the room environment comfortable and the temperature accurate.

*Follow me function is available for KJR-12B, KJR-29B and KJR-90C model.

Setting addresses


With the address setting function, and easy for the installation and future service. The service person can set the address for indoor unit by KJR-10B, KJR-29B and KJR-90C.



Control system


Built-in timer

Built-in daily timer offers the convenience of automatically starting and stopping the system at set times.



Easy connection

The wired controller conveniently connects to the indoor unit's display panel via connecting wire.



Specifications

Model	10B	12B
Dimensions (H×W×D)(mm)	120×120×15	120×120×15
Power (V)	DC 5V	

Wired Controller



KJR-90A



KJR-86C



KJR-120B

Functions

Features

- Small and easy to install
- Suitable for all types of indoor units
- Can be stored in a mounting cabinet

Built-in timer


Built-in daily timer offers the convenience of automatically starting and stopping the system at set times.



KJR-90A

Mode setting

Mode-button hidden controller: Press the temperature buttons "▲" and "▼" simultaneously for 3 seconds to select the operation mode: COOL and HEAT. The design is suitable for hotels, hospitals, schools and other similar types of buildings.



KJR-86C

Auto mode

For V4 plus R series used only. Under the auto mode of V4 plus R system, it can automatically switch to COOL or HEAT mode according to the temperature difference value between Tf(indoor temperature) and Ts(setting temperature)



KJR-120B

Specifications

Model	90A	86C	120B
Dimensions (H×W×D)(mm)	90×86×13	86×86×18	120×120×20
Power (V)	DC 5V		

Wired Controller

HRV Wired Controller KJR-27B



Functions

HRV controller


KJR-27B is individually designed for HRV—Heat Recovery Ventilator. The HRV can work in the following modes: exhaust, air supply, bypass, heat exchange, and auto.

**AUTO->HEAT EXCHANGE->
EXHAUST->BYPASS->AIR SUPPLY**

Built-in timer

Built-in daily timer offers the convenience of automatically starting and stopping the HRV at the set times.

Setup screen example
Set to wednesday: 8:00 to 20:00



Specifications

Model	KJR-27B
Dimensions(H×W×D)(mm)	120×120×15
Power (V)	198-242V(50/60Hz)

Weekly Schedule Controller

MD-CCM04 KJR-120C



Functions

Simple design

MD-CCM04 can be used as a weekly schedule wired controller or general wired controller. It can query the indoor temperature and the setting parameters of the weekly schedule. It can display the error codes and running state of the indoor unit. With the LCD backlight, and allows users to operation the device in a dark room.

Delay function

The function is specially designed for a person who is working overtime. During the weekly schedule running, press delay button it will delay 1 hour or 2 hours to turn off the air conditioner.

Weekly schedule

Users can set up to 4 periods schedule per day, and select the desired running mode and room temperature.

	8:00	16:00	23:59
Sun	28°C	22°C	24°C
Mon	26°C	22°C	17°C
Tue	26°C	22°C	17°C
Wed	26°C	22°C	17°C
Thu	26°C	22°C	26°C
Fri	26°C	22°C	26°C
Sat	28°C	off	24°C

Specifications

Model	MD-CCM04	KJR-120C
Dimensions (H×W×D)(mm)	120×120×15	120×120×20
Power (V)	DC 5V	DC 12V

Centralized Controller


Indoor Centralized Controller



MD-CCM03



CCM30




Functions

Centralized control

The centralized controller is a multifunctional device that can control up to 64 indoor units within a maximum connection length of 1,200m.

The device connects to the master outdoor units of Koolman's newly designed products to simplify and centralize the wiring configuration. The 2 ways of connecting are as follow:



*If it connects to XYE ports of master ODU, ODU must be set to auto addressing mode.


Three lock modes

Centralized controller provides a superior way to manage the indoor units. Users are able to make their own choice from locking the wireless controller, locking the running mode or lock the centralized controller's keyboard as they wish.




Indoor unit working status display

The centralized controller displays indoor units' working status and error codes so users can easily identify faults via checking the error codes table in the user's manual before contacting a service engineer.



Air filter cleaning reminding function

The air filter cleaning reminder function is only available on the touch-key central controller CCM30. The "FL" icon indicates that the air filter in a given indoor unit needs cleaning.



Functions


Stylish design

CCM's stylish design suits high-end environments. The keyboard lock function is used to prevent operational mistakes.




Single/unified control

The control object can be either a single unit or all units, which vastly simplifies the control process. Operation signal feedback ensures that all units are working in the correct mode.




Easy installation

Centralized controller offers two different appearances to mostly suit the installation. The A structure must be embedded into the wall and the B structure doesn't need. Both of them are easy to operate.



*The A,B structure is available for CCM30, and MD-CCM03 only has B structure




B structure leading-out mode sketch

Control system

Access to network monitoring

The centralized controller is able to bridge up to 64 indoor units on the network monitoring and building management systems.



Specifications

Model	MD-CCM03		CCM30	
Dimensions (H*W*D)(mm)	179×119×74		180×122×78 and 180×122×68	
Power (V)	198-242V(50/60Hz)			

Centralized Controller

Weekly Schedule Centralized Controller

MD-CCM09



Auto mode



COOL mode



HEAT mode



Fan mode



DRY mode



Swing



Keyboard lock



Cooling lock



Heating lock



Remote controller lock



Weekly schedule

Functions

Weekly schedule

MD-CCM09 can include up to 64 indoor units in the weekly schedule. Users can set up to 4 periods per day, and select the desired running mode and room temperature. The operating object can be a single indoor unit or all the indoor units.

	8:00		16:00	23:59
Sun	28°C	22°C	24°C	
Mon	26°C	22°C	17°C	23°C
Tue	26°C	22°C	17°C	23°C
Wed	26°C	22°C	17°C	23°C
Thu	26°C	22°C		26°C
Fri	26°C	22°C		26°C
Sat	28°C	off		24°C


Three lock modes

Centralized controller MD-CCM09 provides a superior way to manage the indoor units. Users are able to make their own choice from locking the wireless controller, locking the running mode or lock the MD-CCM09's keyboard as they wish.



Single/unified control mode

The control object can be either a single unit or all units, which vastly simplifies the control process. Operation signal feedback ensures that all units are working in the correct mode.



Indoor unit working status display

MD-CCM09 displays indoor units' working status and error codes so users can easily identify faults via checking the error codes table in the user's manual before contacting a service engineer.

*If it connects to XYE ports of master ODU, ODU must be set to auto addressing mode.

Error code or protection code				Connecting status matrix															
Current	ALL	Set, temp	Mode	Auto	Query Set Opr, unsuccess														
88	Online	ON	OFF	Error	88	1	2	3	4	5	6	7	8	9	10	11	12	13	14
12A	12B	13	Period	Room, temp	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88
Week	Sun	Mon	Tue	Wed	Thu	Fri	Sat												
88	18	38	38	38	38	38	38												
				Fan															
				Weekly Timer															

Specifications

Model	MD-CCM09
Dimensions (H*W*D)(mm)	179×119×74
Power (V)	198-242V(50/60Hz)

Centralized Controller

Unified On/Off Controller
KJR-90B

Unified controller design with graceful appearance and explicit panel.
Can control single or group indoor units.



Functions

Unified control

KJR-90B offers on/off and heating/cooling functionality for indoor units based on preset temperatures to ensure easy management.



Centralized control

KJR-90B can be used to centrally control up to 16 indoor units.




Light indicator

The LEDs on KJR-90B indicate the indoor units' running status for easy fault detection. The lights switch off automatically to save energy once a given operation is complete. The indicators are as follows:

Light	Blue	Red	Flash
Single On/Off key	Cooling/Fan	Heating	IDU Error
Unified On/Off key			EEPROM Error

Easy installation

KJR-90B can be easily mounted on the built-in cabinet:



Specifications

Model	KJR-90B
Dimensions (H*W*D)(mm)	90×86×8
Power (V)	DC 5V

Centralized Monitor

Outdoor Centralized Monitor

MD-CCM02



Query parameters



4-way/EXV valve



Protection/Error codes



Power consumption



With the ODU communication



With the PC communication




Forced Cooling

Functions

ODU parameters display

MD-CCM02 enables users to easily check outdoor units' running status, including frequency, temperature, current, pressure, protection codes and error codes.



Graph 2 LCD Screen

Access to network monitoring

MD-CCM02 can connect up to 8 refrigerant systems and 32 outdoor units to the network system.



Specifications

Model	MD-CCM02
Dimensions(H×W×D)(mm)	120×120×15
Power (V)	198-242V(50/60Hz)

Central Control Software



Central Control Software

IMM(Intelligent Manager of Koolman) 4th Generation Network Control System




Functions

Intelligent Manager of Koolman, designed specifically to control VRF systems, is based on a centralized format and dedicated to the complete control and monitoring of all the system's functions. It can be used as a flexible multi-purpose system and applied to a variety of needs, according to the scale, purpose and control method of each building.

- Up to 4 M-interfaces, 64 refrigerant systems, 1,024 indoor units, and 256 outdoor units can be controlled by one PC.
- Web Access
- User friendly operation
- Central building monitoring and control
- Energy saving management
- SMS modem (optional)
- Electricity charge distribution
- Schedule management
- Low-load operation indicate
- Generate operational history reports (daily, weekly, monthly)
- Fault display & Warning message
- Air filter cleaning reminding function
- Emergency stop and Alarm signal output

Network Control Application



- Can run on Window 7_32/64 bit, Window XP_32 bit and Window 8.
- Can monitor and control A/C anytime, anywhere by PC, iPhone, iPad and notebook computer.
- Support WEB access: IE, Firefox, Safari and Chrome.
- Enables remote access through DSL, VPNs and so on.

Various Managements



Simple Operation and Management

Click & Operate, a user-friendly interface allows even non-experts to perform the building management system easily.

Data Management

Operational information of individual indoor units are monitored, allowing for distribution of power consumption at outdoor units.

Stores operation data on multiple systems and displays it in graphical format for visual management.

Uses IMM software to generate tenant reports and help building owners bill for energy use.

Electricity Charge Distribution(Patented)

Provides information on proportional electrical power distribution to optimize electricity consumption management.

Uses software to calculate electric power proportional distribution, output and save electricity consumption data for each indoor unit (or group) which is connected to the intelligent manager.

Applies the patented Koolman Calculation Method to calculate consumption rates according to capacity demand which is based on various parameters: setting temperature, room temperature, running mode, rated HP, public areas, unused rooms, and nighttime use; outputs this information on a charge calculation sheet to evenly divide power consumption charges among tenants.

Highlights



Web Access function

With the web access function, a PC, laptop computer or a smart phone can be used as a remote controller.



Visual Navigation

Clicking the jump button will display a list of all available screens. Clicking the back button will return to the previous screen.



Energy Saving Management

Based on a predetermined schedule, the Intelligent Manager executes capacity control and intermittent operations on all air conditioning units to maintain a high comfort index.



Data Backup

The M-interface will automatically back up data on the installed SD card (2GB) in case system failure occurs, such as: power failure or system dam. IMM software also stores the previous 3 months' operational data on the HDD.



Schedule Control

Automatically performs facility start/stop control, switches the operating mode, sets temperatures and enables/disables the remote control according to the present time schedule. 4 sections and 20 actions per day for each single unit or group.



Multiple Languages

Provides seven language settings:

English	French	Italian
Russian	German	Spanish
Simple Chinese		



Warning Message

The system can receive error messages from air conditioning units in more than one buildings or structures via public phone lines.

*Requires the Koolman "SMS Modem" to send automatic warning messages to designated phone numbers.



Electricity Charge Distribution

Electricity charges can be easily divided when billing users for air conditioning power charges; for example, for tenants in a commercial building, offices in a rented building, or rooms in a hotel.

Accessories

Data converter


CCM15

- Can realize data conversion between TCP/IP protocol and 485 protocol.
- WEB function realizes VRF system's webpage access.
- Through LAN and remote to query and control the air conditioners.
- Providing the TCP / IP port for VRF system of Koolman to achieve WEB/HTTP/TCP/IP access.
- Can control and query the A/C systems through computer, iPhone, iPad or other intelligent terminals.



Network example

- Can be directly connected with XYE port of the indoor/outdoor units.
- Up to connect 64 indoor units.
- CCM03/CCM30 is optional and can be connected with CCM15 through F1F2E ports.
- The system consisting A/C system, data converter CCM15, router, cloud server and control terminal.



*If it connects to XYE ports of master ODU, ODU must be set to auto addressing mode.

Simply control interface

- Software control/ Cloud server control (WEB access).
- Click & operate, a user-friendly interface.
- Allows single and group control.
- Simplified user control interface.
- Colour indication and icon makes it easy to recognize unit state.
- Can full screen display and temperature can be adjusted by fingers' sliding.



Weekly schedule control

- With weekly schedule function for iPad and Web function.
- Multiple sections in each day for single unit or group.
- Automatically performs facility start/stop control, operating mode, setting temperatures and according to the present time schedule.



Web features

- Query and control single unit or group.
- Weekly schedule setting: can set multiple sections in each day for single unit or group.
- Group user control : a user can use the same ID to manage hundreds of CCM15, when selecting the "As group user" button on the login page.
- History error: easy service and management with history error function.

Intelligent control

- The air conditioner remote control can be realized by mobile phone or tablet computer.
- You can query and control the running state of the air conditioner any time and any where and even make an appointment in advance.
- Can remotely turn off the air conditioner to avoid the power waste, when you are in a hurry to leave.



Accessories

BACnet® BMS Gateway


MD-CCM08

Contains 4 groups of RS485 communication ports and be able to connect up to 256 indoor units or 128 outdoor units to the BMS.
Be free to connect to the BMS or not.
Built-in WEB function.



Network example

Each port can connect to XYE ports of IDU/ODU or the K1K2E ports of the outdoor units.
Each port can also connect to one CCM03 or one CCM02 through F1F2E ports.








*If it connects to XYE ports of master ODU, ODU must be set to auto addressing mode.

Monitoring units online

MD-CCM08 allows users to track units' operational status and change their running parameters on Internet Explorer for maximum control convenience.

Wide compatibility

CCM08 has a wonderful adaptability to the BMS

	Company	BMS software	Brand
1	SIMENS	APOGEE	
2	TRANE	Tracer Summit	
3	Honeywell	Alerton	
4	Schneider	Andover	
5	Johnson	METASYS	

Accessories


Modbus BMS Gateway CCM-18A

Supports Modbus protocol networks
Bridges the Koolman central A/C system to BMS
Connect up to 64 or 16 indoor units and 4 outdoor units
Built-in WEB server function
*4 outdoor units must be in the same system




Network example

1) TCP connection method



2) RTU connection method



*1. If it connects to XYE ports of master ODU, ODU must be set to auto addressing mode.
2. XYE and K1K2E must be connected hand by hand.

Config A/C System via Web



When the Modbus network is set, users can conveniently configure their A/C network system over the Internet using different TCP/IP browsers.

Accessories

LonWorks® BMS Gateway

MD-LonGW64

Compliance with LonMark protocol, and realizes the management and control of A/C.


Can connect up to 64 indoor units to the BMS.

Realizes non-polarity communication, and also the application can be download online.




Network example

Connection method 1: Suitable for all of air conditioner systems and connect max.64 indoor units.



BMS system

Connection method 2: Only suitable for V4 plus system and connect max.64 indoor units.



BMS system

*If it connects to XYE ports of master ODU, ODU must be set to auto addressing mode.

Specifications

Model	MD-LonGW64
Dimensions (H*W*D)(mm)	319×251×61
Power (V)	177~265V AC(50Hz/60Hz)

Accessories

3-Phase Protector

HWUA/DPB71CM48

Detect the power condition and make the corresponding protecting action.

Protect the compressor from being damaged.

Automatically distinguish the abnormal power supply conditions and automatically recover.



HWUA DPB71CM48

Excellent reliability

The protector protects the entire system from power supply problems, and auto restart after recovery.

Specifications

Model	With over/under voltage function				Without over/under voltage function
	HWUA	DPA53CM23	HWUA	DPB71CM48	DPA51CM44
Power supply (V-N-Hz)	220~480V-3N 50/60Hz	208~480V-3N 50/60Hz	220~480V-3N 50/60Hz	380~480V-3N 50/60Hz	208~480V-3N 50/60Hz
Temp. range(°C)	-20 °C~50 °C	50Hz: -20 °C~60 °C 60Hz: -20 °C~50 °C	-20 °C~50 °C	-20 °C~50 °C	50Hz: -20 °C~60 °C 60Hz: -20 °C~50 °C
Rated operational power(VA)	2.9 VA	7 VA	2.9 VA	13 VA	13 VA
Over voltage	12%	12%	18%	18%	/
Under voltage	-12%	-12%	-12%	-12%	
Phase imbalance	8%	/	8%	8%	
Dimensions(W×H×D)(mm)	90×69×35	81×67.2×17.5	90×69×35	81×67×35	81×67.2×17.5

Digital Power Ammeter

DTS634/DTS636

Calculates power consumption.

Does not need adjusting after long-term use.

Corresponds one outdoor unit to one digital power meter.



Control system


Low power consumption

The digital power meter consumes minimal energy.

Voltage circuit: less than 2W/10VA

Current circuit: less than 2.5VA

Indications and installation



The digital power meter is tested after manufacture so it can be immediately deployment and used on-site. The LED indicators and installation schematic are shown in the figure on the left.

Specifications

Model	DTS634/DTS636
Dimensions (H*W*D)(mm)	230×145×72
Power (V)	200V-500V(50/60Hz)

Remote Alarm Controller

KJR-32B



Functions

Simple design

KJR-32B is specially designed for engineering applications. It does not display the ODU's working parameters, but it can connect to the alarm device when ODU is working abnormally, the RUN light will flash.

Specifications

Model	KJR-32B
Dimensions (H*W*D)(mm)	150×85×70
Power (V)	198-242V(50/60Hz)

Indoor Unit Group Controller

KJR-150A




Functions

Simple design

KJR-150A is a indoor group controller, designed specifically for V4 plus indoor units. It can connect up to 16 indoor units through XYE ports.

With a display panel connected to KJR-150A, signal from wired controller and remote controller can control a group of indoor units simultaneously and all indoor units will run at the same setting parameters. You can also control the indoor units separately in each room by remote controller. The indoor unit will run at the state according to the latest setting.

System wiring diagram



* If you need to use a centralized controller, you can connect to the XYE from an outdoor unit.

Specifications



Model	KJR-150A
Dimensions (H*W*D)(mm)	150×85×70
Power (V)	198-242V(50/60Hz)

Accessories

Infrared sensor controller

MD-NIM09

Automatically adjust the room environment.
Automatically extend the shutting down time, avoiding frequent ON/OFF.
Graceful appearance accommodates itself to different buildings.



Remote controller or wired controller can control indoor unit.



Specifications

Model	MD-NIM09
Dimensions(H×W×D)(mm)	Senor part: 46×30×25.6, Control box: 86×72.8×15.5
Power	DC 5V

Hotel Card Key Interface Module

MD-NIM05

Cooperate with the wired controller to automate control.
Eliminates the need for high voltage power, making the device safe and steady.
Includes a build-in auto-restart function.
Remote controller or wired controller can control indoor unit.



Specifications

Model	MD-NIM05
Dimensions (H*W*D)(mm)	86×72.8×15.5
Power (V)	DC 5V

Accessories

AHU Control Box

AHUKZ-01A/AHUKZ-02A/AHUKZ-03A


V4+ functions inside.

Can be used to connect VRF outdoor units with DX AHU or other brand indoor units



Introduction

AHUKZ-01A/AHUKZ-02A/AHUKZ-03A is an independent control box that can connect a AHU to V5 plus system to realize centralized control with V5 plus system. Control box wiring is as follows:



Specifications


Model	AHUKZ-01A/AHUKZ-02A/AHUKZ-03A		
Dimensions(H×W×D)(mm)	335×375×150		
Power (V)	220-240V~ 50Hz	208-230V~ 60Hz	

Koolman Outdoor Unit Diagnosis Software MCAC-DIAG/E

Display the outdoor units' real-time running conditions.


Automatically outputs running status charts.

Supports V3, V4, V4+, D3, D4, V4+S and V4+R outdoor units.



Wiring diagram

The diagnostic software applies to K1, K2, E of the outdoor units. The corresponding wiring diagram is shown in the figure on the right.



Recommended config

Operating system	WIN XP SP4/WIN 7
CPU	Pentium 4 2G or above
HDD	30G free space
Interface port	RS-232 terminal

Selection software

To meet consultants' and distributors' requirements, Kooman has developed an advanced design automation tool that can be used in AutoCAD-based CAD version or Windows-based Sales version. The software provides quick and convenient selectable options for users, supports multiple languages, and greatly improves the selection process.

Windows Version


Load calculation: Provides two calculation methods (detailed room load calculation and rough load calculation).

Indoor & outdoor units selection: There are versatile indoor units and different outdoor units for choosing.

Piping drawing: Displays the detailed layout of an A/C system and the parameters for piping and branch distributors.

Controller selection: Provides a selection of controllers for indoor units and outdoor units, including wireless and remote controllers for indoor units.

Report output: Outputs a comprehensive selection report as a Word or PDF document.



CAD Version



AutoCAD add-on software

Automatic Calculation: Refrigerant & drain pipe size

Automatic Selection: Distributor kit & branch joint

System Check: Installation regulation & refrigerant addition

Automatic Report: Piping installation diagram, equipment list & quotation



HRV

Heat recovery ventilator

Larger air supply rate
enhanced heat exchange efficiency
enhanced energy saving property


The heat recovery ventilator (HRV) can reclaim heat energy lost through ventilation and reduce the room temperature fluctuation caused by ventilation process. By utilizing the most advanced technology and technics, Koolman HRV has extremely good performance. The heat exchanged core is made of special paper processed with chemical treatment, which could realize better temperature and humidity control of the room environment. Temperature exchange efficiency is above 65% and enthalpy exchange efficiency between 50-65%.

Model Names

HRV-200	HRV-500
HRV-300	HRV-800
HRV-400	HRV-1000



HRV-1500 HRV-2000




Low noise

Sound proof material is used to guarantee quiet operation.

Compact design, flexible installation and easy maintenance

With a min. height of only 10-25/64in.(264mm) and 50lbs (23kg) weight, the unit provides best convenience and possibility for installation in limited spaces.




Multi-modes for different situations

Heat exchange mode

When air flow formed by the fans goes through the heat exchanged core in cross way, due to temperature difference between two channels of the core, thermal transmission happens naturally.

In summer days, high temperature outdoor air gets cooled by indoor exhaust air; in winter, low temperature outdoor air gets heated by indoor exhaust air. So the energy contained in exhaust air can be reclaimed and energy efficiency gets improved.


Heat exchange mode



Bypass mode

In mild climate areas or seasons, when temperature and humidity level difference between indoor and outdoor is small, the unit works as conventional ventilation fan. Both supply fan and exhaust fan works at the same speed (Hi/mid/low/auto).

Bypass mode



Air supply mode

It is one kind of bypass mode with air supply fan speed higher than exhaust fan speed. It can be used in mild climate area where large amount fresh air is needed.

Exhaust air mode


It is also one kind of bypass mode with exhaust fan speed higher than air supply fan speed. It can be used in mild climate area where large amount exhaust air needs to be expelled.

Auto mode

The controller chooses heat exchange mode or bypass mode according to the temperature difference between outdoor and indoor temperature. Both the two fans work at low speed.

Flexible control

Interlocking control with other indoor units by controller is possible.



Specifications

Model				HRV-200	HRV-300	HRV-400	HRV-500					
Power supply			V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50 (220/1/60)	220-240/1/50 (220/1/60)					
Cooling	Temperature exchange efficiency	High	%	55	55	55	55					
		Medium	%	55	55	55	55					
		Low	%	60	60	60	60					
	Enthalpy exchange efficiency	High	%	50	50	50	50					
		Medium	%	50	50	50	50					
		Low	%	55	55	55	55					
Heating	Temperature exchange efficiency	High	%	60	60	60	65					
		Medium	%	60	60	60	65					
		Low	%	65	65	65	70					
	Enthalpy exchange efficiency	High	%	55	55	60	60					
		Medium	%	55	55	60	60					
		Low	%	60	60	65	65					
Sound pressure level	Heat exchange mode	High	dB(A)	27	30	32	35					
		Medium	dB(A)	26	29	31	34					
		Low	dB(A)	20	23	25	28					
	Bypass mode	High	dB(A)	28	31	33	36					
		Medium	dB(A)	27	30	32	35					
		Low	dB(A)	22	25	27	30					
Net dimension (W×D×H)			mm	866×655×264		944×722×270		944×927×270		1038×1026×270		
			inch	34-1/8×25-3/4×10-3/8		37-3/16×		37-3/16×36-1/2×10-5/8		40-7/8×40-3/8×10-5/8		
Packing size (W×D×H)			mm	930×730×445		1010×800×450		1010×1010×450		1120×1120×452		
			inch	36-5/8×28-3/4×17-1/2		39-3/4×31-1/2×17-3/4		39-3/4×39-3/4×17-3/4		44-1/8×44-1/8×17-13/16		
Net/gross weight			kg(lbs)	23/40		26/44		31/52(68.3/114.4)		41/64(90.4/140.8)		
Casing				Galvanized steel plate								
Heat exchange system				Air to air cross flow total heat (sensible heat + latent heat) exchange								
Heat exchange element material				Specially processed nonflammable paper								
Fan	Type			Centrifugal fan								
	Airflow rate	High	m³/h(CFM)	200		300		400(235.6)		500(294.5)		
		Medium	m³/h(CFM)	200		300		400(235.6)		500(294.5)		
		Low	m³/h(CFM)	150		225		300(176.7)		375(220.8)		
	ESP	High	Pa	75		75		80		80		
		Medium	Pa	58		60		65		68		
		Low	Pa	35		40		43		45		
Motor output			W		20		40		80		120	
Duct diameter			mm(in.)	Φ144		Φ144		Φ144(5-5/8)		Φ194(7-5/8)		
Operating temperature range			℃	-7~43 DB, 80% RH or less								
			℉	19.4~109.4 DB, 80% RH or less								

Model				HRV-800	HRV-1000	HRV-1500	HRV-2000	
Power supply			V/Ph/Hz	220-240/1/50 (220/1/60)	220-240/1/50 (220/1/60)	380-415/3/50 (280/3/60)	380-415/3/50 (280/3/60)	
Cooling	Temperature exchange efficiency	High	%	55	55	55	55	
		Medium	%	55	55	/	/	
		Low	%	60	60	/	/	
	Enthalpy exchange efficiency	High	%	50	50	50	50	
		Medium	%	50	50	/	/	
		Low	%	55	55	/	/	
Heating	Temperature exchange efficiency	High	%	65	65	65	65	
		Medium	%	65	65	/	/	
		Low	%	70	70	/	/	
	Enthalpy exchange efficiency	High	%	60	60	60	60	
		Medium	%	60	60	/	/	
		Low	%	65	65	/	/	
Sound pressure level	Heat exchange mode	High	dB(A)	39	40	51	53	
		Medium	dB(A)	38	39	/	/	
		Low	dB(A)	32	33	/	/	
	Bypass mode	High	dB(A)	40	41	52	54	
		Medium	dB(A)	39	40	/	/	
		Low	dB(A)	34	35	/	/	
Net dimension (W×D×H)			mm	1286×1006×388		1286×1256×388	1600×1270×540	1650×1470×540
			inch	50-5/8×39-5/8×15-1/4		50-5/8×49-7/16×15-1/4	63×50×21-1/4	65×57-7/8×21-1/4
Packing size (W×D×H)			mm	1380×1100×573		1390×1350×580	1680×1350×720	1760×1580×720
			inch	54-5/16×43-5/16×22-9/16		54-3/4×53-1/8×22-13/16	66-1/8×53-1/8×28-3/8	69-5/16×62-3/16×28-3/8
Net/gross weight			kg(lbs)	62/88(136.7/193.6)	79/110(173.8/242)	163/224(358.6/492.8)	182/247(400.4/543.4)	
Casing				Galvanized steel plate				
Heat exchange system				Air to air cross flow total heat (sensible heat + latent heat) exchange				
Heat exchange element material				Specially processed nonflammable paper				
Fan	Type			Centrifugal fan				
	Airflow rate	High	m³/h(CFM)	800(471.1)	1000(588.2)	1500(882.4)	2000(1176.5)	
		Medium	m³/h(CFM)	800(471.1)	1000(588.2)	/	/	
		Low	m³/h(CFM)	600(353.4)	750(441.2)	/	/	
	ESP	High	Pa	100	100	160	170	
		Medium	Pa	82	85	/	/	
		Low	Pa	54	58	/	/	
	Motor output			W	360	360	450	450
Duct diameter			mm(in.)	Φ242(9-1/2)	Φ242(9-1/2)	346×326(13-5/8×12-7/8)	346×326(13-5/8×12-7/8)	
Operating temperature range			°C	-7~43 DB, 80% RH or less				
			°F	19.4~109.4 DB, 80% RH or less				

Note:

1. For the units model of HRV (400-1000), there are 3-speed adjustable air volume (Hi, Med, Low), but for the units model of HRV (1500-2000), there are only 1-speed which cannot be adjusted.

2. Sound level is measured at 1.4m below the center of the body in an anechoic chamber.

3. Efficiency is measured under the following conditions:





* Cooling Condition: Air Exhaust Temp. 27°C(80.6°F) DB,19.5°C(67.1°F) WB., Fresh Air Temp. 35°C(95°F) DB,28°C(82.4°F) WB.

* Heating Condition: Air Exhaust Temp. 21°C(69.8°F) DB,13°C(55.4°F) WB., Fresh Air Temp. 5°C(41°F) DB,2°C(35.6°F) WB.

Branch Pipe






Branch Pipe

Branch joints of two-pipe refrigerant system

Model	Appearance	Model name	Packing Size in.(mm)	Gross Weight lbs.(kg)	Description
Branch joint for 410A outdoor unit		FQZHW-02N1D	10-1/16×5-7/8×7-1/4 (255×150×185)	3.3(1.5)	For two outdoor units connection
		FQZHW-03N1D	13-9/16×6-5/16×11-1/4 (345×160×285)	7.48(3.4)	For three outdoor units connection
		FQZHW-04N1D	18-3/4×6-1/2×11-3/4 (475×165×300)	10.56(4.8)	For four outdoor units connection
Branch joint for R410A indoor unit		FQZHN-01D	11-7/16×4-1/8×4 (290×105×100)	0.88(0.4)	A*<16.6kW
		FQZHN-02D	11-7/16×4-1/8×4 (290×105×100)	1.32(0.6)	16.6≤A*<33kW
		FQZHN-03D	12-3/16×5-1/8×4-15/16 (310×130×125)	1.98(0.9)	33kW≤A*<66kW
		FQZHN-04D	13-25/32×7-3/32×6-11/16 (350×180×170)	3.3(1.5)	66kW≤A*<92kW
		FQZHN-05D	14-3/8×7-11/16×8-15/32 (365×195×215)	4.18(1.9)	92kW≤A*

A*:The total capacity of indoor units which is connected to this branch joint

Branch joints of three-pipe refrigerant system

Model	Appearance	Model name	Packing Size in.(mm)	Gross Weight lbs.(kg)	Description
Branch joint between outdoor unit		FQZHW-02SB	10-11/16×6-9/16×9-1/8 (272×167×232)	4.84(2.2)	For two outdoor units connection
		FQZHW-03SB	18-9/16×6-3/16×12-9/32 (472×157×312)	11(5.0)	For three outdoor units connection
		FQZHW-04SB	29-5/16×6-5/16×13-3/16 (745×160×335)	16.5(7.5)	For four outdoor units connection
Branch joint between MS unit and outdoor unit		FQZHN-01SB	10-1/8×5×4-7/32 (257×127×107)	1.76(0.8)	A* < 16.6kW
		FQZHN-02SB	11-5/16×5-3/8×4-7/32 (287×137×107)	1.98(0.9)	16.6 ≤ A* < 33kW
		FQZHN-03SB	11-11/16×6-9/16×6-31/32 (297×167×177)	3.08(1.4)	33kW ≤ A* < 66kW
		FQZHN-04SB	14-5/8×7-3/4×7-3/8 (372×197×187)	5.06(2.3)	66kW ≤ A* < 92kW
		FQZHN-05SB	17-1/64×8-3/4×8-15/16 (432×222×227)	7.26(3.3)	92kW ≤ A*
Branch joint between MS unit and indoor unit		FQZHN-01D	11-7/16×4-1/8×4 (290×105×100)	0.88(0.4)	A* < 16.6kW

A*:The total capacity of indoor units which is connected to this branch joint

Dimensions

Outdoor branch joints

Branch model	Gas side joints	Liquid side joints
FQZHW-02N1D		
FQZHW-03N1D		
FQZHW-04N1D		

Branch pipes

Dimensions

Indoor branch joints

Branch model	Gas side joints	Liquid side joints
FQZHN-01D		
FQZHN-02D		
FQZHN-03D		
FQZHN-04D		
FQZHN-05D		

Branch pipes